

● FEATURES



1080P 1/3" CMOS 20μm 4.7μm 94.0μm WDR

1 7.0" IR 120
Max.25 / 30fps @ 1080p

2 TI 368 H.264; MJPEG

3 DWDR/ICR/DNR/2D&; 3D BLC

4 CMS

5 300°/ s 0° 360° 0° 90°

6 128; 4

7 ;

8 -10°C + 50°C

9

[IP](#)

● SPECS



360° 90°	
0.1° 220°/ 0.1° 180°/ s	
IR 100m	
128 ;	
;	
4 ;	
;	
; PTZ	
;	
;	
TVS	
SPEC	
OS	LINUX RTOS 32 DSP TI DM368
RAM	32M 128M DDR2
Encoder	H.264 0.1M-6Mbps

規格	2.0 幀/秒@ 25fps 1-25 FPS;
解析度	1920×1080, 1280×720;
支援解析度	640×360 480×270 352×288 320×240 352×192 288×192 256×192;
網路	10/100Mbps IP
功能	RTSP / FTP / PPPOE / DHCP / DDNS / NTP / UPnP WEB OSD UC2 VM6000 SDK
SPEC	
感光元件	1/3" SONY 322 CMOS
解析度	1920×1080
鏡頭	
視角	58.16°-2.9°
放大倍率	4.7 94
最低照度	20
最低照度	0.02 LUX
功能	
SPEC FUNCTION	WDR
功能	
IRCF	* /
功能	1.0 0.01
功能	DSP-8
功能	* / R B UP/DOWN
IRCF	* /
網路	
網路	10Base-T / 100BASE-TX RJ45
解析度	1920 * 1080
幀率	25/30 fps
編碼	H.264 / MJPEG
功能	
ONVIF	ONVIF 2.4
功能	TCP / IP. HTTP. DHCP. PPPoE. UDP. RTP / RTCP. DNS. DDNS . UPnP. SMTP
視角	0.2° 200° /
視角	0.2° 100° / s
視角	200° / S
旋轉	360° 0° 90°
功能	
功能	128
功能	90° 180°
功能	355° 4
功能	4
功能	
功能	
功能	
OSD	
功能	
溫度	-20°C + 60°C
功能	0 95
功能	IP66
功能	AC24V / 40W IR
功能	6.5



● EXHIBITIONS

