

# H.265 4MP Videoüberwachung IP-System-Ethernet-Kamera (MVT-M2892)

## ● FEATURES



- Nimmt 4,0Megapixel Progressive Scan CMOS-Sensor mit niedriger Beleuchtung an.
- Unterstützt vernetztes Video von H.264 HP H.265 4MP @15fps, 3MP @25fps Auflösung.
- **VandalismusProof Dome** (Metallgehäuse)
- Eingebaut: 3mm Megapixel 6mm CS-Objektiv, POE und DC12V, Audio Ein- / Ausgang, Nachtsicht 30 Meter.
- Standard RTSP und FLASH Video unterstützt, Internet Explorer, Firefox, Safari, Chrome, Opera usw. unterstützen
- Unterstützung Zweiweg sprechend zwischen Kamera mit Fern PC oder Handy durch Internet.
- Android und IOS P2P kostenlose App, kostenloses CMS.
- Angepasste Full-featured ONVIF-Version mit guter Konkurrenzfähigkeit mit Main Stream 3. CMS und NVRs

## ● SPECS



### **Full HD, vernetzt**

- Hochleistungs-DSP mit H.265-Videokomprimierungscode.
- Optimierter intelligenter Codierungsalgorithmus für ein klareres Video mit geringerer Bandbreite.

### **Vertrauenswürdige Qualität**

- Vollmetallgehäuse, Präzisionsdesign, Vandalensicheres Gehäusedesign.
- Beleuchtung Prottech mit 6Kv, Elektrostatik von 8Kv mit Leistungsaufnahme Schutz.

### **Vollständige Funktionalität**

- Dome-Gehäuse-Design, gut zu halten Consistent und einfach für DIY-Decken-und Wandmontage.
- Audio und Video Mixed Surveillance unterstützt.
- Bilit-in IEEE802.3af POE.

<b>Features</b>		POE, Audio In/Out Cable, Powerful IR, DC12V, ONVIF 2.4, Free CMS, P2P Mobile and PC Remote Access
<b>Cameras</b>	Solution	Hi3516D+OV4689
	Sensor	1/3" CMOS
	Min. Illumination (Color)	0.01Lux/F1.2
	Shutter	1/5s-1/50,000s
	Day&Night	IR-CUT Auto, Black, Color
	Images Settings	Images, D&N Mode, Automatic Iris, Metering, White Balance, Exposure, Shutter, Mirror, Noise
<b>Codec</b>	Video Resolution	4.0M(2592*1520)@15FPS, 3M@25FPS
	Codec	H.265
	Video Frames	Real Time, Max 25fps
	Codec Mode	VBR/CBR
	Data Rate	Three Streams, Main: 1500kbps-8Mbps Sub: 50-1000kbps
	Frames	1-30 frame adjustable
	Record	Video and Audio Recording and Playback, MP4 Format
<b>Network</b>	Internet	QR Scan for Remote Surveillance, Free P2P, No Port Forwarding Needed. Free DDNS
	Network Video	Standard RTSP, FLASH
	Remote Access	QR Scan Free APP (iphone/Andriod Smartphone), WEB (IE/Safari/Chrome/Firefox/Opera), NVR, CMS
	Compatibility	Onvif 2.4 and latest version, Customized compatibility with main stream CMS and NVRs
	WIFI	NO
	POE	Inside, IEEE802.3af
	Network Protocol	P2P,RTP,RTSP,TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP
<b>Advanced</b>	System	Time Sync. (Auto/Mannual/NTP/PC/NVR/RTC) Online upgrade /Alarm /System Status Reports
	Audio&Video	Audio (G.711A/U) / Video (Three Streams) / Video Mask / Motion Detection
	Storage	NVR, Cloud
	Events/Security/Log	Events (Events Setting/Schedule Recording/Schedule FTP and Snapshot), Security (Filter of User and IP Address), Log (System/Alarm/Access etc.)
<b>Hardware</b>	Network Interfaces	RJ-45, 10/100Base-T
	Microphone	NO
	Audio via Cable	Audio In/Out, Talkback (G.711A, G.711U)
	Local Storage	NO
	Others	NO
	Application	Indoor and Outdoor
	Installation	Wall-mounting, Ceiling-mounting
	Accessories	CD: 01.User Manual ; 02.CMS and User Manual; 03.IPCManager Tool and User Manual.  Others: Printed Quick-Start, Installation Location Lable, Installation Kits.
	Power Supply	DC12V & POE
	Work Temperature	-10°C-50°C
	Work Humidity	10%-90%
Power Consumption	2 Watt	

## ● FACTORY & OFFICE

M' TEAM



## ● EXHIBITIONS

M' TEAM

