

Modell	MVT-CV62A
Sensor	1/3 "CMOS Pixelplus 1,0 M / 720P
SIGNAL	PAL / NTCS
Video-Ausgang	HD-CVI
Wirkungsvolle Pixel	1280 (H) * 720 (V)
Minute Erleuchtung	0,05 Lux @(F1,2, AGC EIN), 0 Lux mit IR-
Shutter	1 / 3s~1 / 100.000 s, unterstützt lange Verschluss
Video Frequency	1280 × 720 @ 50 fps;1280 × 720 @ 60 fps
Synchronisation	Interne
Video-Ausgang	1-Kanal-BNC HDCVI High-Definition-Video-Ausgang
Lärminderung	3DNR
OSD	Support koaxiale Steuer
Belichtung	Belichtungsmodus / Belichtungsstufe / Belichtungsgeschwindigkeit / Anti Flicker / Backlight-Modus
AWB	Automatisch / manuell / Tag / Nacht
Tag Nacht	Auto (ICR) / Farbe / S / W-
Function Set	3DNR / Digitalverstärker / Objektivtyp
Erweiterte Funktionen	Kamera-ID / Spiegel / dynamische Erkennung / Privacy Masking / Sprache / 485 Satz / Systeminformationen
Bildeinstellung	Sharpness / Helligkeit / Kontrast / Sättigung / Schärfe Hemmung / a Farbunterdrückung / gamma / Schalter
Getriebe-Abstand	Über 500 m über 75-3 Koaxialkabel
Energieversorgung	DC 12V ± 10%
Arbeitsumfeld	30 ° C ~ + 60 ° C / Weniger als 95% RH (keine Kondensation)
Energieverbrauch	8W MAX



HD-CVI

High Definition Composite Video Interface

① Introducing HD-CVI

Use Your Existing
Coax Cable



True HD Quality



Extremely
Cost Effective

② This will change everything!

Go From This



This is traditional
cctv system vedio effect

To This!



This is HD-CVI
720P Full Size

Highlights

- HD 720P Video on coax.
- Long Distance Transmission up to 1600ft.
- Video,RS485 and sound over one cable.

③ Benefits

- Upgrade to Megapixel Quality on your coax cable!
- Long Rane Runs up to 1600ft!
- One Cable for Video,RS485 and Audio!
- No Signal Loss!
- Around the same price as the older analog CCTV technology!



Video



RS485



Easy Install



Audio

P2P-Funktion AV orteile:

- * **Benötigen Sie nicht tun, stabile IP-Adresse Setup**
- * **Benötigen Sie nicht tun, DDNS Setup**
- * **Benötigen Sie nicht tun, Router-Setup**
- * **Reduzieren Sie Ihre After-Sales-Kosten**

HD-CVI CCTV Camera and DVR

- * Low cost high definition surveillance system
- * Support long-distance HD transmission
- * Same installation way as traditional CCTV system

720P HD-CVI camera

1/2.9"CMOS ,1.0M/720P,with IR CUT(PO3100)



MVT-CV11A

Gray and White color optional,
with 6mm Lens,36pcs×Φ5 IR leds,
30m IR Distance,
3-Axis bracket with cable built-in



MVT-CV21A

Gray and White color optional,
with 2.8-12mm vari-focal Lens,
42pcs×Φ5 IR leds,
35m IR Distance,
bracket with cable built-in



MVT-CV73A

with 8mm Lens,
2 pcs 3rd generation LED Array,
50m IR Distance,with bracket



MVT-CV74A

with 16mm Lens,
4 pcs 3rd generation LED Array,
100m IR Distance,with bracket

720P Display&Record HD-CVI DVR



MVT-CV6304

1-4CH 720P
2-Video output:BNCx1,VGAx1,HDMIx1
3-Support 1pc hard disk
4-Support P2P network view



MVT-CV6404H

1-4CH 720P
2-Video output:BNCx1,VGAx1,HDMIx1
3-Support 2pcs hard disk
4-Support P2P network view
5-Support Alarm input:4CH,Alarm output:1CH



MVT-CV6504

1-4CH 720P
2-Video output:BNCx1,VGAx1,HDMIx1
3-Support 2pcs hard disk
4-Support P2P network view
5-Support Alarm input:4CH,Alarm output:1CH



MVT-CV6508

1-8CH 720P
2-Video output:BNCx1,VGAx1,HDMIx1
3-Support 2pcs hard disk
4-Support P2P network view
5-Support Alarm input:4CH,Alarm output:1CH

● FACTORY & OFFICE

M'TEAM



● EXHIBITIONS

M'TEAM

