

## FEATURES



•

• 1.0M / 1.3M / 2.0M 1080P

• HD / CVBS

• 6M12

• IP66

• 753 500M

•

• OSD

• ICR

• LED

•

•

## SPECS



Model	MVT-AH20A	MVT-AH20N	MVT-AH20E	MVT-AH20T	MVT-AH20B	MVT-AH20P
CMOS	1/4 "CMOS pixelplus 1.0M / 720P OV9712	1/4 "CMOS pixelplus 1.0M / 720P AR0141	1/3 "CMOS pixelplus 1.3M / 1024P AR0131	1/3 "CMOS pixelplus 1.3M / 1024P AR0130	1/3 "CMOS pixelplus 1.3M / 1024P SONY225	1/3 "CMOS pixelplus 2.0M / 1080P SON322
SIGNAL	PAL / NTCS					
Interface	HD-AHD / CVBS					
Resolution	1280H* 720V	1280H* 720V	1280H* 1024V	1280H* 1024V	1280H* 1024V	1920H* 1080V
Sensitivity	0.01Lux F1.2					
Frame rate	4 / 25S / 45,000s					
Mount	DIN					
Input	1 BNC HDAHD / CVBS					
BLC	On/Off					
OSD	On/Off					
AWB	On/Off/0					
ICR	On/Off/ B / W					
Power	75-3 500M					
Voltage	DC 12V±10%					
Operating Temp	30°C+ 60°C/ 95%RH					
Power Consumption	4W MAX					



Blue color



White color



\* Mini Style

\* Lens 3.6mm&6.0mm optional  
\* IR LED 24pcs,IR 20m



firm bracket, angle adjustable

M TEAM

## ● FACTORY & OFFICE

M'TEAM



## ● EXHIBITIONS

M'TEAM

