

● FEATURES

M'TEAM

1. IP66 4 360° 90° 0.1° 300° / 0.1° 180°

2. 10X

3. 128 4 4 4 8
0.01°

4.

5. 3D-NR

6. Lightningproof

7. 1/3 222 CMOS 200 / 1080 10 ICR

● SPECS

M'TEAM

PTZ	
PTZ	0.2° 300° / 0.2° 180°
DC	DC 12V
PTZ	360° 0° 90°
PTZ	
Resolution	128
PTZ	90° 180°
PTZ	355° 4
PTZ	4 180S
PTZ	4 & 038;
Remote	RS485
PTZ RS485	2400/4800/19200 9600 BPS
ID	1-254
PTZ	6W

°C	-10°C~50°C/ -40°C~60°C 0.038; 0.000000
0.000000	0.000000 0.000000
0.00 0.00	1.800
CAM	
0.000	1/3 " 322 CMOS + SONY4191 ISP * 1080 1920
0.00	X10 F = 5.1 51
0.00	APPR 55.2° 3.2°
0.00 0.00	0.5 BW 0.1lux
S / N Y	52
0.000 0.000	0.000
ICR	0.000/0.000
DNR	0.00 / 0.00 / 0.00 / 0.00
HLC	0.00 / 0.00
0.000 0.000	0.000
0.00	0.000
FLIP	0.00 0.00 OFF 0.000

● PRODUCT PICTURE



● FACTORY & OFFICE

M' TEAM



● EXHIBITIONS

M' TEAM

