

H.265 4MP 2592 * 1520 IP MVT-M2992

FEATURES



- 4.0 CMOS
- H.264 HP H.265 4MP @15fps 3MP @25fps
-
- 2.8 12V POE DC12V / 30
- RTSP FLASH Internet Explorer Firefox Safari Chrome Opera
- PC
- Android iOS P2P CMS
- ONVIF 3 CMS NVR

SPECS



HD

- H.265 DSP
-

-
- Prottech 6Kv 8Kv

- DIY
-
- Built-in IEEE802.3af POE

| | | |
|-------------------|---------------------------|---|
| Features | | POE, Audio In/Out Cable, Powerful IR, DC12V, ONVIF 2.4, Free CMS, P2P Mobile and PC Remote Access |
| Cameras | Solution | Hi3516D+OV4689 |
| | Sensor | 1/3" CMOS |
| | Min. Illumination (Color) | 0.01Lux/F1.2 |
| | Shutter | 1/5s-1/50,000s |
| | Day&Night | IR-CUT Auto, Black, Color |
| | Images Settings | Images, D&N Mode, Automatic Iris, Metering, White Balance, Exposure, Shutter, Mirror, Noise |
| Codec | Video Resolution | 4.0M(2592*1520)@15FPS, 3M@25FPS |
| | Codec | H.265 |
| | Video Frames | Real Time, Max 25fps |
| | Codec Mode | VBR/CBR |
| | Data Rate | Three Streams, Main: 1500kbps-8Mbps Sub: 50-1000kbps |
| | Frames | 1-30 frame adjustable |
| | Record | Video and Audio Recording and Playback, MP4 Format |
| Network | Internet | QR Scan for Remote Surveillance, Free P2P, No Port Forwarding Needed. Free DDNS |
| | Network Video | Standard RTSP, FLASH |
| | Remote Access | QR Scan Free APP (iphone/Andriod Smartphone), WEB (IE/Safari/Chrome/Firefox/Opera), NVR, CMS |
| | Compatibility | Onvif 2.4 and latest version, Customized compatibility with main stream CMS and NVRs |
| | WIFI | NO |
| | POE | Inside, IEEE802.3af |
| | Network Protocol | P2P,RTP,RTSP,TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP |
| Advanced | System | Time Sync. (Auto/Mannual/NTP/PC/NVR/RTC) Online upgrade /Alarm /System Status Reports |
| | Audio&Video | Audio (G.711A/U) / Video (Three Streams) / Video Mask / Motion Detection |
| | Storage | NVR, Cloud |
| | Events/Security/Log | Events (Events Setting/Schedule Recording/Schedule FTP and Snapshot), Security (Filter of User and IP Address), Log (System/Alarm/Access etc.) |
| Hardware | Network Interfaces | RJ-45, 10/100Base-T |
| | Microphone | NO |
| | Audio via Cable | Audio In/Out, Talkback (G.711A, G.711U) |
| | Local Storage | NO |
| | Others | NO |
| | Application | Indoor and Outdoor |
| | Installation | Wall-mounting, Ceiling-mounting |
| | Accessories | CD: 01.User Manual ; 02.CMS and User Manual; 03.IPCManager Tool and User Manual. Others: Printed Quick-Start, Installation Location Lable, Installation Kits . |
| | Power Supply | DC12V & POE |
| | Work Temperature | -10°C-50°C |
| | Work Humidity | 10%-90% |
| Power Consumption | 2 Watt | |



M TEAM

● FACTORY & OFFICE

M' TEAM



● EXHIBITIONS

M' TEAM

