

● FEATURES



□□□□

1. □□□□□□□□
2. □□□□□□□□
3. □□□□AHD DVR□□□□□□□□□□DVR□□□□□□□□□□
4. □□□□□□□□□□□□
- 3G□□□□□□□□□□5. Advanced CMS□□□□□□

□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□

● SPECS



□□□	MVT-D3441O	MVT-D3441F	MVT-D3441Z
□□□□□□□□	1/4 " □ □□CMOS	1/3 " □ □□CMOS	1/3 " □ □□CMOS
□□□□□□□□	PAL / NTSC		
□□□□□□	PAL□582 □V□×752□H□	PAL□582 □V□×752□H□	PAL□582 □V□×976□H□
	NTSC□494□V□ ×768□H□	NTSC□494 □V□×768□H□	NTSC□494□V□ ×976□H□
□□□□□□	600TVL	600TVL	700TVL
□□□□□□	□ □□□□0.003□0.6□□□□□□□□□□OFF□□B / W □□□□□0.0001□0.1□□□□□□□□□□OFF□		
S / N□Y□□□□	> 58□□□□		
AES	1 / 50-1 / 60,000sec□PAL□□1 / 60-1 / 60,000sec□NTSC□		
WDR	-	-	-
DNR	-	-	-
OSD	-	-	-

□□□□□□□□	ATW / AWC / □□□□□□ / □□□□□□ □1800°K□10500°K□□□□□4500°K□8500°K□
AGC	AUTO
BLC	□
□□□□□□	0.45
□□□□□□	□□□ □□
□□□□□□	1.0Vp-p□□75Ω
□□	DC12V □9V□15V□
□□□□□□	-20°C□60°C / 10□□95□RH

● PRODUCT PICTURE



● FACTORY & OFFICE

M'TEAM



● EXHIBITIONS

M'TEAM

