

● FEATURES



1080P 1/3 CMOS 1.3M 10 53.2°-5.65° WIDE-TELE

1 4

2 IR 25 35

3 / ICR AWB AGC BLC

4 0° 360°

0° 90°

300°/

4

8

5 & 038; 4

[IP PTZ](#)

● SPECS



360° 90°	
0.1° 220° / 0.1° 180°/	
IR 35	
128	
& 038;	
PTZ	
TVS	
SPEC	
1 / 2.3 " AR0130 1.3M CMOS	
68° / 6.7°	
5.1 51	
10	
0.02LUX	
IRCF	* /
	1.0 0.01
	HIS3516C
	* / R B UP DOWN
IRCF	* /
DSP	HIS3518A + AR0130
IR	35

通訊協定	10BASE-T / 100BASE-TX / RJ45
幀率	25/30 FPS
編碼	H.264 / MJPEG
通訊協定	ONVIF
ONVIF	ONVIF 2.4
通訊協定	TCP / IP.HTTP.DHCP.PPPoE.UDP.RTP / RTCP.DNS.DDNS .UPnP.SMTP
旋轉	0.2°~200°/s
旋轉	0.2°~100°/s
旋轉	200°/S
旋轉	360°; 0°~90°
旋轉	0°~360°/0°~90°
旋轉	128 個位置
旋轉	180°~90°
旋轉	355° 1°
旋轉	1 個位置
OSD	是
旋轉	是
溫度	-20°C~+ 60°C
溫度	0~95°C
防護	IP66 防塵防水
電源	DC12V / 24W 紅外線
尺寸	2.5寸

● PRODUCT PICTURE



● FACTORY & OFFICE

M'TEAM



● EXHIBITIONS

M'TEAM

