

● FEATURES



**1080P** 1/3 CMOS 1.3 10 53.2°-5.65° WIDE-TELE

1 4 IR 60 70

2 / ICR AWB AGC BLC

3 0° 360°  
0° 90°  
200°/

4 128  
4  
8

5 & 038;

6

[IP PTZ](#)

● SPECS



360° 90°	
0.1° 220° / 0.1° 180°	
IR 60	
128	
& 038;	
PTZ	
TVS	
SPEC	
1 / 2.3 " AR0130 1.3M CMOS	
68° / 6.7°	
5.1 51	
10	
0.02 LUX	
IRCF	* /

精度	±1.0%±0.01%±0.01%
型号	HIS3516C
报警功能	报警*/报警R 报警/ B报警报警UP/DOWN
IRCF报警	报警*/报警报警
DSP	HIS3518A + AR0130
IR	60
网络	10BASE-T / 100BASE-TX RJ45
帧率	25/30 FPS
编码	H.264 / MJPEG
报警	报警
ONVIF	ONVIF 2.4
协议	TCP / IP.HTTP.DHCP.PPPoE.UDP.RTP / RTCP.DNS.DDNS .UPnP.SMTP
报警	报警0.2°±200°/
报警	报警0.2°±100°/
报警	200°/ S
报警	报警 360°;报警报警0°90°报警
报警	报警 报警/报警
报警	128报警报警报警报警报警
报警	报警报警90° 报警报警180°
报警	355° 报警报警报警1报警
报警	1报警报警报警报警报警报警
OSD	报警
报警	报警
报警	-20°C + 60°C
报警	0~95报警报警
报警	IP66 报警报警报警
报警	DC12V / 24W IR 报警
报警	2.5



● EXHIBITIONS

