

## FEATURES



1. 1080P Full HD
2. 1080P Full HD
3. AHD DVR / H.264 DVR
4. 1080P Full HD
- 3G / 5.0 CMS

## SPECS



| Model          | MVT-R73410   | MVT-R7341F       | MVT-R7341Z       | MVT-R7341E       | MVT-R7341A | MVT-R7351E       | MVT-R7351F       |
|----------------|--|------------------|------------------|------------------|------------|------------------|------------------|
| Resolution     | 1/4" CMOS  | 1/3" CMOS        | 1/3" CMOS        | 1/4" CMOS        | 1/3" CMOS  | 1/3" CCD         | 1/3" CCD         |
| Standard       | PAL / NTSC   |                  |                  |                  |            |                  |                  |
| Format         | PAL 582<br>752H                                      | PAL 582<br>752H  | PAL 582<br>976H  | PAL 582<br>976H  | 720P       | PAL 582<br>976H  | PAL 582<br>976H  |
|                | NTSC 494<br>768H                                     | NTSC 494<br>768H | NTSC 494<br>976H | NTSC 494<br>976H |            | NTSC 494<br>976H | NTSC 494<br>976H |
| TVL            | 600TVL   | 600TVL           | 700TVL           | 800TVL           | 1000TVL    | 700TVL           | 700TVL           |
| Sensitivity    | 0.003 / 0.6 OFF / B / W 0.0001 / 0.1 OFF             |                  |                  |                  |            | 0.01LUX / F1.2   | 0.01LUX / F1.2   |
| S/N            | > 58dB   |                  |                  |                  |            | > 65dB AGC OFF   |                  |
| AES            | 1 / 50-1 / 60,000sec PAL / 1 / 60-1 / 60,000sec NTSC |                  |                  |                  |            |                  |                  |
| WDR            | -  | -                | -                | -                | -          | D-WDR            | D-WDR            |
| DNR            | -  | -                | -                | -                | -          | 2D-DNR           | 2D-DNR           |
| OSD            | -  | -                | -                | -                | -          | OSD              | OSD              |
| Temperature    | ATW / AWC / 1800°K / 10,500°K / 4500°K / 8500°K      |                  |                  |                  |            |                  |                  |
| AGC            | AUTO   |                  |                  |                  |            | ON / OFF         |                  |
| BLC            | ON   |                  |                  |                  |            | ON / OFF         |                  |
| Gain           | 0.45   |                  |                  |                  |            |                  |                  |
| Impedance      | 75Ω  |                  |                  |                  |            |                  |                  |
| Power          | DC12V / 9V / 15V                                     |                  |                  |                  |            |                  |                  |
| Operating Temp | -20°C / 60°C / 10%~95%RH                             |                  |                  |                  |            |                  |                  |



## New Appearance CCTV Cameras



**MVT-R46**  
8mm(CS) Lens,  
42 pcs IR leds



**MVT-R30**  
8mm Lens,  
42pcs×Φ5 IR leds



**MVT-R21**  
2.8-12mm  
vari-focal Lens,  
42pcs×Φ5 IR leds



**MVT-R62**  
2.8-12mm  
vari-focal Lens,  
42pcs×Φ5 IR leds



**MVT-R58**  
9-22mm  
vari-focal Lens,  
72pcs×Φ5 IR leds



**MVT-D30**  
6mm lens,  
24pcs×Φ5 IR leds



**MVT-D22**  
6mm lens,  
36pcs×Φ5 IR leds



**MVT-D28**  
6mm lens,  
36pcs×Φ5 IR leds



**MVT-D29**  
2.8-12mm  
vari-focal Lens,  
36pcs×Φ5 IR leds



**MVT-D26**  
2.8-12mm(M12)  
vari-focal Lens

## ● FACTORY & OFFICE

M TEAM



## ● EXHIBITIONS

M TEAM



□□□□□□ □□□□ □□□□□□□□□□ □□□□□□