

360 stopni ukryta kamera CCTV Kryty VR Wifi Żarówka Kamera H100-E

● FEATURES

M'TEAM

- * Zastosuj matrycę CMOS o wysokiej rozdzielczości 1.3MP, 2MP, 3MP dla Twojej opcji
- * Szeroki kąt widzenia 360 stopni, bez ślepego obszaru, dotyczy różnych scenariuszy, obsługując 4 różne tryby oglądania
- * Obsługa dwukierunkowego dźwięku, odpowiedzi głosowe.
- * Automatyczny przełącznik filtra podczerwieni ICR, realizuje rzeczywisty monitoring w dzień i w nocy
- * Obsługa standardowej rozdzielczości HD, aby oglądać, aby dostosować się do różnych środowisk sieciowych
- * Wsparcie monitorowania w czasie rzeczywistym telefonów komórkowych
- * Obsługa sterowania PTZ, zdalne przechwytywanie, nagrywanie dźwięku i obrazu
- * Globalny zasięg sieci, zawsze i wszędzie sprawny zegarek
- * Obsługa aplikacji mobilnej N_eye 3C

Easy installation, Screw it easily

Led bulb shape, standard E27 base, AC 220V voltage.



Multi-Angle Monitor


Support multi-scene modes



E PTZ



SPLIT SCREENS



ROLLER



CORRIDER

Video footage storage

Support max 128GB micro TF card for recording.



—▶ 8:30 —▶ 14:30 —▶ 20:08 —


Note: Memory cards not included in the package
please purchase separately



Intergrated with LED illumination



Show Appearance



Mobile Phone View



Download the App



Scan QR code to download the APP or
Search Neye3C in APP Store/Android Market



Model No.		H100-E6	H100-E8	H100-E9
Camera	Resolution	1.3MP	2.0MP	3.0MP
	Minimum illumination	0.02Lux @(F2.0,AGC ON) ,0 Lux with IR		
	Shutter	Shutter adaptation		
	Camera lens	360 degree fisheye lens		
	Lens interface type	M12		
	Day and night conversion	ICR infrared filter		
	Digital noise reduction	3D digital noise reduction		
Compression	Video compression standa	H.264		
	Coding type	H.264 Main Profile		
	Video compression rate	HD, SD, rate adaptation.		
	Audio compression standa	AAC		
	Audio compression rate	Rate adaptation		
	Frame rate	Max:25fps network transmission rate: adaptive adjustment		
	Image setting	Brightness, contrast, saturation, etc. (through the client to adjust the setting)		
Network	Storage function	Support Micro SD card (max 128G)		
Function	Intelligent alarm	Video is lost, the network is disconnected, and the power is disconnected.		
	General functions	Reverse, capture, mobile alarm, password protection, video playback, remote control, two-way intercom		
Wireless	Wireless standard	IEEE802.11b, 802.11g, 802.11n Draft		
Parameter	frequency range	2.4 GHz ~ 2.4835 GHz		
	Channel bandwidth	Support 20/40MHz		
	security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS		
	transmission speed	11b: 11Mbps, 11g :54Mbps, 11n :135Mbps		
General specification	temperature and humidity	-		
	Power	AC 110V~220V		
	Power consumption	3W MAX		
	Infrared radiation distance	MAX 5meter		
	Size(mm)	87mm x 87mm x 127mm		
	Weight	200g		

▼ Shipping
M'TEAM






Wysyłka □: Na podstawie twoich żądań wybierz najlepszy sposób wysyłki.

Skontaktuj się z nami:

Jeśli masz jakieś pytanie, zapraszamy [Skontaktuj się z nami](#).

Twoja ścisła uwaga na naszą firmę jest bardzo ceniona.
Zapraszamy do odwiedzenia naszej oficjalnej strony internetowej www.mvteamcctv.com

Powiązane artykuły o Wifi IP Camera:

[Jak ustawić detekcję ruchu dla Wifi IP Camera?](#)

[Jak długie nagrania wideo może zaoszczędzić na karcie TF dla kamer WiFi?](#)

[Jak zdalnie przeglądać kamerę IP WiFi MVTEAM na komputerze?](#)