

- Przyjmuje 4.0Megapixel Progressive Scan CMOS ze słabego oświetlenia.
- Obsługuje Sieciowe wideo H.264 HP H.265 4MP @15fps 3MP @25Rozdzielczość fps.
- **WandalDowód Dome** (Metalowa obudowa)
- Wbudowany w: 3.6mm lub 6mm megapikselowy obiektywPOE i DC12V, Audio in / out, Night Vision 20 metrów.
- Standardowy RTSP i Flash Video Obsługiwane, Pomoc Internet Explorer, Firefox, Safari, Chrome, Opera, itp
- Wsparcie Two Way Mówiąc między aparat fotograficzny ze zdalnego komputera lub telefonu komórkowego za pośrednictwem Internetu.
- Android i IOS P2P Free App, CMS Darmowe.
- Dostosowane pełni funkcjonalnym ONVIF wersja z Dobrego Competibility z Main Stream 3 CMS i NVR

### **Full HD, Networked**

- Wysoka wydajność DSP kod kompresji H.265 za pomocą wideo.
- Zoptymalizowany inteligentnego algorytmu kodowania dla bardziej jasne Wideo z mniejszej szerokości pasma.

### **Sprawdzony Jakość**

- Full Metal Shell, Precyzja Projekt, Wandalooodporna Projekt mieszkaniowy.
- Oświetlenie Prottech z 6kV, elektrostatyczne 8 kV o ochronie wejściowego zasilania.

### **Pełna funkcjonalność**

- Opatentowana konstrukcja obudowy, Dobra Keep Consistent i łatwy do samodzielnego sufitu i montażu na ścianie.
- Mieszane Audio i Video Surveillance Obsługiwane.
- Bilit w IEEE802.3af POE.

<b>Features</b>		POE, Audio In/Out Cable, Powerful IR, DC12V, ONVIF 2.4, Free CMS, P2P Mobile and PC Remote Access
<b>Cameras</b>	Solution	Hi3516D+OV4689
	Sensor	1/3" CMOS
	Min. Illumination (Color)	0.01Lux/F1.2
	Shutter	1/5s-1/50,000s
	Day&Night	IR-CUT Auto, Black, Color
	Images Settings	Images, D&N Mode, Automatic Iris, Metering, White Balance, Exposure, Shutter, Mirror, Noise
<b>Codec</b>	Video Resolution	4.0M(2592*1520)@15FPS, 3M@25FPS
	Codec	H.265
	Video Frames	Real Time, Max 25fps
	Codec Mode	VBR/CBR
	Data Rate	Three Streams, Main: 1500kbps-8Mbps Sub: 50-1000kbps
	Frames	1-30 frame adjustable
	Record	Video and Audio Recording and Playback, MP4 Format
<b>Network</b>	Internet	QR Scan for Remote Surveillance, Free P2P, No Port Forwarding Needed. Free DDNS
	Network Video	Standard RTSP, FLASH
	Remote Access	QR Scan Free APP (iphone/Andriod Smartphone), WEB (IE/Safari/Chrome/Firefox/Opera), NVR, CMS
	Compatibility	Onvif 2.4 and latest version, Customized compatibility with main stream CMS and NVRs
	WIFI	NO
	POE	Inside, IEEE802.3af
	Network Protocol	P2P,RTP,RTSP,TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP
<b>Advanced</b>	System	Time Sync. (Auto/Mannual/NTP/PC/NVR/RTC) Online upgrade /Alarm /System Status Reports
	Audio&Video	Audio (G.711A/U) / Video (Three Streams) / Video Mask / Motion Detection
	Storage	NVR, Cloud
	Events/Security/Log	Events (Events Setting/Schedule Recording/Schedule FTP and Snapshot), Security (Filter of User and IP Address), Log (System/Alarm/Access etc.)
<b>Hardware</b>	Network Interfaces	RJ-45, 10/100Base-T
	Microphone	NO
	Audio via Cable	Audio In/Out, Talkback (G.711A, G.711U)
	Local Storage	NO
	Others	NO
	Application	Indoor and Outdoor
	Installation	Wall-mounting, Ceiling-mounting
	Accessories	CD: 01.User Manual ; 02.CMS and User Manual; 03.IPCManager Tool and User Manual.  Others: Printed Quick-Start, Installation Location Lable, Installation Kits .
	Power Supply	DC12V & POE
	Work Temperature	-10°C-50°C
	Work Humidity	10%-90%
Power Consumption	2 Watt	



● EXHIBITIONS

