

Main Features:

- 1.0M / 1.3M / 2.0M pixel full optional real-time, high definition 1080P
- The follow-HD and CVBS video standard
- Fixed lens 6mm (M12)
- Waterproof Rating: IP66
- 75- 3 general support under the coaxial cable transmission distance without loss of over 500M
- High-speed, long-distance, real-time transmission
- Support OSD
- IC transition, to reach day and night viewing
- 3rd generation actually imported used IR LEDs and high-resolution megapixel lens, this camera color restoration, image definition, and has been featured as a big performance night vision.

Applications:

Finance, supermarkets, telecommunications, government, schools, airports, factories, hotels, museums and other places to apply the high-resolution requirements.

Model	MVT-AH74A	MVT-AH74B
Sensor	1/4" CMOS pixelplus 1.0M/ 720P OV9712+NVP2431H	SONY238+NVP2431H
SIGNAL	PAL / NTCS	
Video Output	HD-AHD/CVBS	
Effective Pixels	1280(H)*720(V)	1280(H)*1024(V)
Min.Illumination	0.05Lux @Color,0.01Lux B/W	
Shutter	4/25s~1/45,000s	
Video Frequency	1280×720@50 fps;1280×720@60 fps	1280×1024@50 fps;1280×1024@60 fps
Synchronization	Internal	
Video Output	1-channel BNC HDAHD/CVBS high definition video output	
BLC	optional	
OSD	optional	
AWB	Automatic / manual / day / night	
Day/Night	Auto(ICR) / Color / B/W	
Transmission Distance	Over 500m via 75-3 coaxial cable	
Power Supply	DC 12V±10%	

Working Environment	-30°C~+60°C/Less than 95%RH(no condensation)
Power Consumption	4W MAX

● PRODUCT PICTURE

M'TEAM



● FACTORY & OFFICE

M'TEAM



