

4CH 1080P AHD and NVR Hybrid High Definition dvr recorder(6704H80P)

● Features

MTEAM

Adopt Newest HiSilicon
Chipset



New humanized
User Interface



System come with
28 kinds of languages



Adjustable DVR
menu transparency




Support backup video
records to DVR built-in
redundant HDD



Support playback different
time period video records in
one screen, save time on find
useful video records



Hybrid DVR support three
kinds of modes:
full analog channels
analog+digital channels
full digital channels




DVR menu with Ping
command, convenient to do
DVR network testing



With UTC Function,control
analog camera and PTZ camera
on DVR thru coaxial cable



Support P2P remote view
by CMS and IE browser



Come with cloud ID,easy to
realize P2P remote view
by scan the QR Codes



Support remote view,record,
playback, receive motion
detection alarm by Iphone
and Andriod Smartphone



Adopt Newest HiSilicon
Chipset



New humanized
User Interface



System come with
28 kinds of languages



Adjustable DVR
menu transparency




Support backup video
records to DVR built-in
redundant HDD



Support playback different
time period video records in
one screen, save time on find
useful video records



Hybrid DVR support three
kinds of modes:
full analog channels
analog+digital channels
full digital channels




DVR menu with Ping
command, convenient to do
DVR network testing



With UTC Function,control
analog camera and PTZ camera
on DVR thru coaxial cable



Support P2P remote view
by CMS and IE browser



Come with cloud ID,easy to
realize P2P remote view
by scan the QR Codes



Support remote view,record,
playback, receive motion
detection alarm by Iphone
and Andriod Smartphone



- 1.AHD:4CH 1080P@15fps recording
2CH 1080P playback
- 2.HVR:2CH 1080P@25fps Analog + 2CH 1080P@25fps IP recording
2CH 1080P@25fps playback
- 3.NVR:4CH 1080P@25fps IP recording
4CH 1080P@25fps playback
- 4-Audio: 4ch input, 1ch output

Model		6704H80P
Compression		H.264 Standard compression
Operation		Embedded Linux
Image coding-control		Image edit adjustable,both changable and fix stream optional
Dual stream		Can be set up in each channel
Monitor image quality		4*180P(NVR),4*1080P(AHD),
Image dynamic detection		Multiple detection areas in each channel
Video framerate		180P 25FPS/CH NVR ,1080P 15FPS/CH AHD
Image playback quality		NVR 4*180P 25FPS,AHD 2CH 1080P
Video mode		Support manual, automatic, dynamic monitoring, alarm trigger video mode
Backup mode		U disk, USB portable disk, USB burn, Network storage and backup
Operate mode		Mouse, Remote controller,Front Panel Control
login locally		admin and password
Save recording		local hard disk and network
External interface	Video input	180P@25FPS/CH NVR ,1080P@15FPS/CH AHD
	Audio input	4×RCA
	Network interface	10M/100M base-T Ethernet (RJ-45)
	USB connect port	2 x USB 2.0
	RS485	RS485*1
	Alarm input	NO
	Alarm output	NO
	Internal HDD	1 SATA HDD port
	Maximum capacity	Maximum 4TB each SATA
Cell phone monitoring		Support Window Mobile, iPhone,iPad, Android
Power		12V/2A
DVR size		255*45*235mm

Weight	<2.7kg(without HDD)
---------------	---------------------

● PRODUCT PICTURE

M' TEAM



● EXHIBITIONS

M' TEAM



▼ Packages

M' TEAM



▼ Shipping

M'TEAM



Contact us:

If you have any question, welcome to [contact us](#).

Your close attention to our company is highly appreciated.

Welcome to visit our official website www.mvteamcctv.com to view [video demos](#), [download product catalog](#) and read [CCTV technical articles](#).