Custom-made Logo 4MP 3MP Bullet POE IP Camera with Vari-focal Lens(MVT-M1892)

Adopt infrared antireflection panel design, make the camera with better night vision.

Infrared Antireflection Panel

Quality reflective overlay, surface-emitting technology, can magnify the effect of focus, improve product performance and reliability.

HD 3MP 2.8-12mm vari-focal lens(M12 Mount),bring more clear image.

Adjustable Bracket

360°

90°

Size

74mm

74mm

132mm

244mm

IP66 Waterproof Grade,give you more reliable protection

● SPECS

MVTEAM

· Adopts 4.0Megapixel Progressive Scan CMOS Sensor with Low Illumination.

· Supports Networked Video of H.264 HP 4MP@15fps 3MP@25fps Resolution.

· IP66,WaterProof

· Built-in: 6mm megapixel lens, POE and DC12V, Audio in/out, Night Vision 30 meters.

· Standard RTSP and FLASH Video Supported,Support Internet Explorer, Firefox, Safari, Chrome, Opera etc

· Support Two Way Speaking between Camera with Remote PC or Mobile Phone through Internet.

· Customized Full Featured ONVIF Version with Good Competibility with Main Stream 3rd CMS and NVRs

Applications:

Finance, supermarkets, telecommunications, government, schools, airports, factories, hotels, museums and other places to apply the high-resolution requirements.

Model	MVT-M1892
Features	POE, Audio In/Out Cable, Powerful IR, DC12V, ONVIF 2.4, Free CMS,
	P2P Mobile and PC Remote Access

Cameras	Solution	Hi3516D+OV4689
	Sensor	1/3" CMOS
	Min. Illumination (Color)	0.01Lux/F1.2
	Shutter	1/5s-1/50,000s
	Day&Night	IR-CUT Auto, Black, Color
	Images Settings	Images, D&N Mode, Automatic Iris, Metering, White Balance, Exposure, Shutter, Mirror, Noise
Codec	Video Resolution	4MP(2592*1520)@15FPS, 3MP(2048*1520)@25FPS
	Codec	H.264 HP, H.265
	Video Frames	Real Time, Max. 25fps
	Codec Mode	VBR/CBR
	Data Rate	Three Streams, Main: 1500kbps-8Mbps Sub: 50-1000kbps
	Frames	1-30 frame adjustable
	Record	Video and Audio Recording and Playback, MP4 Format
Network	Internet	QR Scan for Remote Surveillance, Free P2P, No Port Forwarding Needed. Free DDNS
	Network Video	Standard RTSP, FLASH
	Remote Access	QR Scan Free APP (iphone/Andriod Smartphone), WEB (IE/Safari/Chrome/Firefox/Opera),
		NVR, CMS
	Compatibility	Onvif 2.4 and latest version, Customized compatibility with main stream CMS and NVRs
	WIFI	NO
	POE	Inside, IEEE802.3af
	Network Protocol	P2P,RTP,RTSP,TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP
Advanced	System	Time Sync. (Auto/Mannual//NTP/PC/NVR/RTC) Online upgrade /Alarm /System Status Reports
	Audio&Video	Audio (G.711A/U) / Video (Three Streams) / Video Mask / Motion Detection
	Storage	NVR, Cloud
	Events/Security/Log	Events (Events Setting/Schedule Recording/Schedule FTP and Snapshot),
		Security (Filter of User and IP Address), Log (System/Alarm/Acceess etc.)

Hardware	Network Interfaces	RJ-45，10/100Base-T
	Microphone	NO
	Audio via Cable	Audio In/Out, Talkback (G.711A, G.711U)
	Local Storage	NO
	Others	NO
	Application	Indoor and Outdoor
	Installation	Wall-mounting, Ceiling-mounting
	Accessories	CD: 01.User Manual ; 02.CMS and User Manual; 03.IPCManager Tool and User Manual.
		Others: Printed Quick-Start, Installation Location Lable, Installation Kits.
	Power Supply	DC12V & POE
	Work Temperature	-10℃-50℃
	Work Humidity	10%-90%
	Power Consumption	2 Watt

Package: MVTEAM Brand Box Or Netural Box Or Specified by customer.

Shipping: Based on the your demands to choose the best shipping way.

Contact us:

If you have any question, welcome to **_Contact us_**.
Your close attention to our company is highly appreciated.
Welcome to visit our official website **_www.mvteamcctv.com_** to view video demos,download product catalog and read CCTV technical articles