



- 1 Built-in OSD menu, can change information and parameter of dome through menu, also can set and call presets, tour, scan, pattern, camera mode and display name etc.
- 2 Horizontal Speed $0.1^{\circ} \sim 220^{\circ}/s$, Vertical Speed $0.1^{\circ} \sim 180^{\circ}/s$
- 3 Screen display position of pan/tilt, zoom, temp inside, direction lable, time and date.
- 4 128 presets (titles can be set); Tour is based on presets, speed & park time of presets can be set.

5 Pan 360° continuously, tilt 90° rotation, auto-flip, manual speed: 0.4°/320°/s.

6 4 pattern, and each record time is not less than 180s.

7 4 scan, support scan between left and right limite at an appointed speed.

8 Auto scan function, and at the same time, dome can still zoom, and run tilt

9 Park action function, can auto-call presets or start-up tour, pattern and scan after dome id for a period of time

10 Communication (support Rs485).

11 Built-in multi-protocols and fully compatible with PELCO-D/PELCO-P

12 IP66 all-day protection cover, built-in constant temperature device.

13 Built-in TVS4000V lightning-proof, surge-proof and wave-proof.

SPECS



| PTZ Specs | |
|--------------------|--|
| Manual speed | Pan 0.1°/300°/s Tilt 0.1°/220°/s |
| Preset speed | 220°/s |
| Rotation | Pan continuously 360°, tilt 0°/90° with auto-flip |
| Speed Proportion | As the length of focus, to auto-adjust the speed |
| Preset | 128 preset, title can be edited |
| Auto-flip | Tilt down 90°, with auto-flip 180° |
| Scan | 355°programmable, 4 scan |
| Decoder | Built-in |
| Video output | Female BNC |
| Remote controlling | RS485 |
| Baud rate (RS485) | 2400/4800/9600/19200 bps |
| ID range | 1/254 |
| Temperature | Outdoor -10°C/+60°C |
| Humidity | 0/95%/non-condensation |
| Protection grade | IP66, lightning-proof, surge-proof, wave-proof, all-day defend cover |
| Power supply | AC 24V ±4V |
| Power consumption | Indoor 10W |
| Temperature | -10°C/+60°C |
| Gross weight | 2.9kg |

| Cam Specs | |
|-------------------|-------------------------------------|
| CMOS | 1/3" Sony322+4191 1920*1280 |
| OPTICS | Optical x20, f = 4.7 mm ~ 84.6.0 mm |
| Angle | Appr. 55.2°(Wide) to 3.2°(Tele) |
| Scanning System | Progressive Scan |
| Min. Illumination | Color : 0.5 lux , BW : 0.1lux |
| S/N (Y signal) | 52dB |
| White Balance | Auto |
| ICR | Manual/Auto |
| DNR | Auto / Off / Low / Middle / High |
| Defog | Off / On |

| | |
|----------|---|
| Max Gain | Auto |
| IRIS | Auto |
| FLIP | Vertical , Horizontal ,Vertical-Horizontal,OFF Selectable |

● FACTORY & OFFICE



● EXHIBITIONS



For more about AHD Products welcome to Visit [FAQ](#)