

Main Features:

1. Economical Security camera
2. Nice image quality and cheap price
3. widely compatible, able to match AHD DVR and All Standalone DVR
4. Easy to operate, Plug and Play
5. Advanced CMS software supporting 3G remote view

Application Places

Apply to the financial, supermarket, telecommunications, government, schools, air ports,

factories, hotels, museums and other places of requirement of high-definition.

| | | |
|----------------------|--|--|
| Model | MVT-D2341N | MVT-D2351A |
| Active Pixel | 976*496 | P: 976*582 N: 976*494 |
| Resolution | 800TVL | 900TVL |
| Video Out | 1.0Vp-p Composite Signal (75ohm) | 1.0Vp-p Composite Signal (75ohm) |
| SYNC | Internal | Internal |
| Sensor | PC1099 | P: ICX811AK N: ICX810AK |
| Minimum Illumination | 0.01Lux | 0.05Lux |
| Gama adjust | 0.45 | 0.45 |
| Electric Shutter | PAL:1/50s-1/100000s NTSC:1/60s-1/100000s | PAL:1/50s-1/100000s NTSC:1/60s-1/100000s |

| | | |
|--------------------------|---|---|
| S/N Ratio | 48dB(min)(AGC closed) | 52dB(min) |
| DNR | - | 3D-DNR |
| AWB | AUTO | ATW/PUSH/USER1/ USER2/ANTI CR/ MANUAL/PUSH LOCK |
| AGC | AUTO | AUTO |
| BLC | - | ON/OFF |
| OSD | - | YES |
| D-WDR | - | - |
| SWDR | - | OFF/Low/Midlow/ Mid/Midhigh/High |
| HLC | - | ON/OFF |
| D-Zoom | - | 1-256 |
| IR-Smart | - | ON/OFF |
| Day/Night | - | Auto□Color□Ext |
| Motion Detection | - | 4 areas optional |
| Language | - | 8 kinds |
| Power | 50mA | 120mA |
| Dissipation | | |
| Power Input | DC12V±1V | DC12V±1V |
| Operation Temperature | Temperature -10°C□+60°C,Humidity less than 85%RH | Temperature -10°C□+60°C,Humidity less than 85%RH |

● PRODUCT PICTURE

M TEAM



● FACTORY & OFFICE

M' TEAM



● EXHIBITIONS

M' TEAM

