FEATURES

Main Features:

• 1.0M/1.3M/2.0M pixel full real time optional,Highest resolution 1080P
•follow HD and CVBS video standard
•6mm(M12) fixed Lens
•Water Resistant Rate:IP66

• support transmission distance above 500M under general 75- 3 coaxial cable without loss

• High-speed, long-distance, real-time transmission
• support OSD menu
• with ICR switching , to achieve Day and Night monitoring

•Used genuinely imported 3rd generation IR LEDs and megapixel high definition lens, these cameras have been featured as great performance in color restoration,image definition and night viewing.

Application Places:
Apply to the financial, supermarket, telecommunications, government, schools, airports, factories, hot els, museums and other places of requirement of high-definition.

SPECS

Model	MVT-AH43A	MVT-AH43N
Sensor	1/4" CMOS pixelplus 1.0M/ 720P OV9712	1/4" CMOS pixelplus 1.0M/ 720P AR0141
SIGNAL	PAL / NTCS	
Video Output	HD-AHD/CVBS	
Effective Pixels	1280(H)*720(V)	1280(H)*720(V)
Min. Illumination	0.01Lux F1.2	
Shutter	4/25s~1/45,000s	
Synchronization	Internal	
Video Output	1-channel BNC HDAHD/CVBS high definition video output	
BLC	optional	
OSD	optional	
AWB	Automatic / manual / day / night	
Day/Night	Auto(ICR) / Color / B/W	
Transmission Distance	Over 500m via 75-3 coaxial cable	

Power Supply	DC 12V±10%
Working Environment	30°C~+60°C/Less than 95%RH(no condensation)
Power Consumption	4W MAX

▼Product Pictures

M'TEAM

▼Size

M'TEAM

● FACTORY & OFFICE

M'TEAM

EXHIBITIONS