

Çin Ürünleri Çevrimiçi Alın H.265 4MP 2592 * 1520 IP Dome Kamera (MVT-M2992)

● FEATURES

M'TEAM

- Düşük Aydınlatma ile 4.0Megapixel Aşamalı Tarama CMOS Sensörü benimser.
- H.264 HP H.265 4MP @ Ağa Bağlı Videoyu Destekler15fps, 3MP @25fps Çözünürlük.
- **Tam Vandal**Kanıtı Dome (Metal kasa)
- Dahili: 2.8 ~ 12mm megapiksel objektif, POE ve DC12V, Ses girişi / çıkışı, Gece Görüş 30 metre.
- Standart RTSP ve FLASH Video Desteklenir, Internet Explorer, Firefox, Safari, Chrome, Opera vb. Desteklenir.
- Uzak PC veya Cep Telefonu ile Kamera arasında İnternet Üzerinden İki Yönlü Konuşmayı Destekleyin.
- Android ve IOS P2P Ücretsiz Uygulama, Ücretsiz CMS.
- Ana Akımlı 3. CMS ve NVR'lerle İyi Uyumluluğu Olan Özelleştirilmiş Tam Özellikli ONVIF Sürümü

● SPECS

M'TEAM

Full HD, Ağa Bağlı

- H.265 Video sıkıştırma Kodunu Kullanan Yüksek Performanslı DSP.
- Daha Düşük Bant Genişliğiyle Daha Net Bir Video İçin Optimize Edilmiş Akıllı Kodlama Algoritması.

Güvenilir Kalite

- Tam Metal Shell, Hassas Tasarım, Vandal Kaliteli Konut Tasarımı.
- 6Kv ile Aydınlatma Prottech, Güç girişi Koruma ile 8Kv Elektrostatik.

Tam İşlevsellik

- Kubbe Konut Tasarımı, İNGİLİZCE Tavan ve Duvar montajı için uygun ve kolay tutun.
- Ses ve Video Karışık Gözetim Desteklenir.
- Bilit-in IEEE802.3af POE.

Features		POE, Audio In/Out Cable, Powerful IR, DC12V, ONVIF 2.4, Free CMS, P2P Mobile and PC Remote Access
Cameras	Solution	Hi3516D+OV4689
	Sensor	1/3" CMOS
	Min. Illumination (Color)	0.01Lux/F1.2
	Shutter	1/5s-1/50,000s
	Day&Night	IR-CUT Auto, Black, Color
	Images Settings	Images, D&N Mode, Automatic Iris, Metering, White Balance, Exposure, Shutter, Mirror, Noise
Codec	Video Resolution	4.0M(2592*1520)@15FPS, 3M@25FPS
	Codec	H.265
	Video Frames	Real Time, Max 25fps
	Codec Mode	VBR/CBR
	Data Rate	Three Streams, Main: 1500kbps-8Mbps Sub: 50-1000kbps
	Frames	1-30 frame adjustable
	Record	Video and Audio Recording and Playback, MP4 Format
Network	Internet	QR Scan for Remote Surveillance, Free P2P, No Port Forwarding Needed. Free DDNS
	Network Video	Standard RTSP, FLASH
	Remote Access	QR Scan Free APP (iphone/Andriod Smartphone), WEB (IE/Safari/Chrome/Firefox/Opera), NVR, CMS
	Compatibility	Onvif 2.4 and latest version, Customized compatibility with main stream CMS and NVRs
	WIFI	NO
	POE	Inside, IEEE802.3af
	Network Protocol	P2P,RTP,RTSP,TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP
Advanced	System	Time Sync. (Auto/Mannual/NTP/PC/NVR/RTC) Online upgrade /Alarm /System Status Reports
	Audio&Video	Audio (G.711A/U) / Video (Three Streams) / Video Mask / Motion Detection
	Storage	NVR, Cloud
	Events/Security/Log	Events (Events Setting/Schedule Recording/Schedule FTP and Snapshot), Security (Filter of User and IP Address), Log (System/Alarm/Access etc.)
Hardware	Network Interfaces	RJ-45, 10/100Base-T
	Microphone	NO
	Audio via Cable	Audio In/Out, Talkback (G.711A, G.711U)
	Local Storage	NO
	Others	NO
	Application	Indoor and Outdoor
	Installation	Wall-mounting, Ceiling-mounting
	Accessories	CD: 01.User Manual ; 02.CMS and User Manual; 03.IPCManager Tool and User Manual. Others: Printed Quick-Start, Installation Location Lable, Installation Kits .
	Power Supply	DC12V & POE
	Work Temperature	-10°C-50°C
	Work Humidity	10%-90%
Power Consumption	2 Watt	



M TEAM

● FACTORY & OFFICE

M' TEAM



● EXHIBITIONS

M' TEAM

