

# 33MP IP MVT-NO704



## FEATURES

**1080P 1/3" Panasonic CMOS 30fps 4.7 mm~155.0 mm WDR P2P**

1 5.5" 120 / 25 / 30fps @ 1080p

2 TI 368 H.264 & MJPEG

3 DWDR ICR DNR 2D 3D AWB AGC BLC

4 Web CMS

5 300° / s 0°~360° 0°~90°

6 128; 4

7 &

8 -10°C + 50°C

9

[IP PTZ](#)



## SPECS

360° 90°	
0.1°~220°/ s 0.1°~180°/ s	
100	
128;	
4	
PTZ	
TVS	
SPEC	
OS	LINUX RTOS 32 DSP TI Davinci DM368
RAM	32M 128M DDR2

規格	H.264 0.1M-6Mbps
規格	200 @ 25fps 1-25 fps;
規格	1920×1080,1280×720; 640×360,480×270,352×288,320×240,352×192,320×192,288×192,256×192;
規格	IO ip
規格	IO
規格	RTSP / FTP / PPPOE / DHCP / DDNS / NTP / UPnP
規格	WEB OSD
規格	UC2 VM6000 SDK;
規格	
規格	
規格	1 / 2.8" Panasonic CMOS 34222
規格	1920×1080
規格	
規格	58.16°-2.9°
規格	4.7 mm~155mm
規格	33
規格	0.02LUX
規格	
SPEC FUNTION	WDR
規格	
IRcf	* /
規格	1.0 TELE 0.01
規格	DSP-8
規格	* / R / B
IRcf	* /
規格	
規格	
規格	10Base-T / 100Base-TX RJ45
Max Imagine Resolution	1920 * 1080
規格	25/30 fps
規格	H.264 / MJPEG
規格	
ONVIF	Onvif 2.4
規格	TCP / IP.HTTP.DHCP.PPPoE.UDP.RTP / RTCP.DNS.DDNS .UPnP.SMTP
規格	0.2° 200° / s
規格	0.2° 100° / s
規格	200° / S
規格	360°; 0~90°
規格	
規格	128
規格	90° 180°
規格	355° 4scan
規格	4
規格	PTZ
規格	
規格	
OSD	
規格	
規格	-20°C + 60°C
規格	0 95

□□□□	IP66□□□□□□□□
□□□□	AC24V / 40W□IR□□
□□	6.5□□

● PRODUCT PICTURE



● FACTORY & OFFICE





www.mvteamcct.com