8CH 720P□□□□NVR□□□□□12.5“□□□□MVT-K08B□

Specfications□

□□ NVR □□		
□□ □□	□□□ Linux□ OS	
AV□□□/□□□□□	□□ □□	8CH
	□□ □□ □□ broadbank	20Mbps□
AV □□□□□□ □□	HDMI □□	1□□□□□□1024x768,1366x768□ 1440x900,1920x1080p
AV CODEC □□	□□ □□□	720P / 960P
	□□□□	8CH

□□ □□	□□□□ □□	Maual□□□□□□
	□□ □□	□□ □□□□□□□□□
	□□	USB □□
□ □□	□□	1 * SATA □□
	□□□ □□	4TB □ □ □□ □
□□ □□	□□ □□	1 □□□□ RJ45 10M / 100M□ 2 □□□□ □□
	USB □□	3 USB 2.0
□□ □□	□□	□□□□□□ □□□□□□□□;□□□□SMTP □□□□□ □ □□□PPPOE □□□□□ DHCP □□□ □□ □□ IP □□□□ □□...
□□	□□	DC12V3A
	□□ □□ □W□	≤5W□□ HDD□
	□□ □□ □C□	-10℃□+ 55℃
	□□ □□ □□□ RH	10□□90□
	□□	257□□□W□×210□□□V□×45□□□H□
	□□□□□□ HDD□	≤1Kg

Wireless Camera Specs	
Image Sensor	1/4" Progressive Scan Sensor
Signal System	PAL/NTSC
Resolution	1280 x 720 16 : 9 High Defination
Minimum illumination	Color: 0.1 Lux; B/W: 0.01 Lux
Shutter	1/25s to 1/25,000s
Lens	3.6mm
OSD	Date Time & Title
White Balance	Auto
Day&Night	Auto / Color / BW
3D-DNR	Auto
Mirror/Flip	On / Off
Frame Specification	Three Streaming at the Same Time H.264 128x720@30fps or below H.264 640x480@30fps or below
S/N	> 39.1 Db
Interface	RJ45 / WIFI 802.11b/g/n
Anti-thunder Level	Standard IEC61000-4-5
Working Temperature/Humidity	-10℃ to +50℃ / 30% to 80% RH
Storage Temperature/Humidity	-20℃ to +60℃ / 20% to 90% RH
Power Input	DC12V-1A
Power consumption	≤6W
Size	205(L)×70(W)×55 (H)mm
Weight	500g
Level of Protection	IP66

□□□□□

Q1-□□□□□□□□□□□□

A1□ □□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

Q2-□□□□□□□□□□□□□□□□□□□□

A2□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□ □□□□□□IE□□□□□□□□□□□□□□□□□□iPhone□Android□

□□□□APP□ESEENET +□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□NVR□□□

Q3- NVR□Camera□□□□□□□□□□□□

A3□ □□□□□□□□□□□□□□□□□□NVR□□□□□ □□

□□□□□□□□□□□□□100m□□□□□□□□□30m□□□□

□□□□□□□□□□□

30m barrier transmit distance

100m transmit distance in open space

□□□□□□□□□□□□□□□□□□□□□

□□□□□
□□□□□□□□□□□□ □□□□□
□□□□□□□□□□□□□□
□□□□□□□□□□□□ www.mvteamcctv.com