

● FEATURES

□□□□

1. □□□□□□
2. □□□□□□□□□□
3. □□□□□□□□ AHD DVR □□□□□□□□□□
4. □□□□□□□□
5. Advanced CMS □□□□ 3G □□□□

□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□

● SPECS

□□	MVT-D3441O	MVT-D3441F	MVT-D3441Z
□□□□□	1/4" □ □CMOS	1/3" □ □CMOS	1/3" □ □CMOS
□□□□	PAL / NTSC		
□□□□□	PAL □752 □H □×582 □V □	PAL □752 □H □×582 □V □	PAL □976 □H □×582 □V □
□□□□□	NTSC □768 □H □×494 □V □	NTSC □768 □H □×494 □V □	NTSC □976 □H □ ×494 □V □□
□□□□□	600TVL	600TVL	700TVL
□□□□	□□ □□□0.003 □0.6 □□□□□□□□ OFF □□ B / W □□□ 0.0001 □0.1 □□□□□□□□□ OFF □		
S / N □Y □□□	> 58 □□		
AES	1 / 50-1 / 60,000sec □PAL □□ 1 / 60-1 / 60,000sec □NTSC □		
WDR	-	-	-
DNR	-	-	-
OSD	-	-	-

□□□	ATW / AWC / □□/□□□1800°K□10500°K□□□ □4,500°K□8500°K□
AGC	□□
BLC	ON
Gamma□□	0.45
□□□□	□□ □□
□□□□	1.0VP-P□75Ω
□□	DC12V □9V□15V□
□□□□	-20°C□60°C / 10□□95□RH□

● PRODUCT PICTURE

M TEAM



● FACTORY & OFFICE

M'TEAM



● EXHIBITIONS

M'TEAM

