

## ● FEATURES

M'TEAM

特點

1. 1080P 30FPS
2. 1080P 30FPS
3. 1080P 30FPS AHD DVR 1080P 30FPS
4. 1080P 30FPS
5. Advanced CMS 3G 3G

特點

1080P 30FPS 1080P 30FPS 1080P 30FPS 1080P 30FPS 1080P 30FPS

## ● SPECS

M'TEAM

|       |                                                     |                                                        |
|-------|-----------------------------------------------------|--------------------------------------------------------|
| 型號    | MVT-D2841N                                          | MVT-D2851A                                             |
| 解析度   | 976 * 496                                           | 976 * 582<br>N 976 * 494                               |
| 解析度   | 800TVL                                              | 900TVL                                                 |
| 解析度   | 1.0VP-P 75Ω                                         | 1.0VP-P 75Ω                                            |
| SYNC  | 內建                                                  | 內建                                                     |
| 解析度   | PC1099                                              | ICX811AK<br>N ICX810AK                                 |
| 解析度   | 0.01LUX                                             | 0.05LUX                                                |
| 解析度   | 0.45                                                | 0.45                                                   |
| 解析度   | PAL 1 / 50S-1 /<br>100000s NTSC 1/60-1<br>/ 100000s | PAL 1 / 50S-1 /<br>100000s<br>NTSC 1/60-1 /<br>100000s |
| S / N | 48dB AGC                                            | 52dB                                                   |
| DNR   | -                                                   | 3D-DNR<br>ATW / PUSH / USER1<br>/                      |
| AWB   | 內建                                                  | 2 / CR /<br>/ PUSH LOCK                                |

|       |                     |                                |
|-------|---------------------|--------------------------------|
| AGC   | □□                  | □□                             |
| BLC   | -                   | □□                             |
| OSD   | -                   | YES                            |
| D-WDR | -                   | -                              |
| □□□□  | -                   | □/□/ Midlow /<br>□/ Midhigh /□ |
| HLC   | -                   | □□                             |
| D-□□  | -                   | 1-256                          |
| IR-□□ | -                   | □□                             |
| □□    | -                   | □□□□□□□□                       |
| □□    | -                   | 4□□□□□                         |
| □□    | -                   | 8□                             |
| □□    | 50□□                | 120□□                          |
| □□    |                     |                                |
| □□□□  | DC12V±1V            | DC12V±1V                       |
| □□    | □□-10°C□+ 60°C□□□□□ | □□-10°C□+ 60°C□□□□□            |
| □□    | □□85%RH□            | □□85%RH□                       |

● PRODUCT PICTURE

MTEAM



## ● FACTORY & OFFICE

M' TEAM



## ● EXHIBITIONS

M' TEAM

