

● FEATURES

□□□□

1. CMOS / CCD □□□
2. □□□□□□□□□□□□□□□□
- 3. □□□□□□□
4. Low □□□□□□□□□□□□□□□□ Environment
5. Lightingproof □□

● SPECS

□□□

- □□□10 □□□□□
- □□□□@ 700TVL / 600TVL
- WDR □ DWDR □□□/□□ ICR □□ DNR □ 2D&□□; 3D □□□□□□□□□□□□□□□□□□□□□□ BLC
- MAX300°/ s □□□□□□□□□□360° □□□□
- □□128 □□□□□4 □□□□□□□4 □□□□4 □□
- □□□□□□□□□□□□□□□□
- 1500V □□□□□□; □□□□□□□□□□-10 □□50°C □□DC12V

□□	MVT-M05
□□□□	□□□0.1° □□300°C/ s □□
□□□□	□□□0.1° □□180°/□□
□□	DC 12V
□□	□□360° □□□□□0 □□90° □□□□
□□□□	□□□□□□/□□□□
□□	128 □□□□□□□□□□□
□□□□	□□90° □□□□□□180°
□□	355° □□□□□4 □□
□□	4 □□□□□□□□□□□□□□□□180 □□□
□	4 □□□
RTC	□□□□□□□□□□□□□□
□□□□	8 □□□□□□□□□□□

□□□□	□□□□□□
Remote □□	RS485
□□□□ RS485 □	2400/4800/9600/19200□□□
ID □□	1-254
□□□□	6W / 9W□□□□
□□	-10°C□+50°C
□□	□□□□□□
□□	1.3□□

● **PRODUCT PICTURE**



● FACTORY & OFFICE

M TEAM



● EXHIBITIONS

M TEAM



████████ AHD ██████████