

● FEATURES



360° 90° 0.2° 300°/s
 40m
 128
 ;
 ;
 4
 OSD
 RS485
 PELCO-D PELCO-P
 TVS DC12V; IP66

● SPECS



CAM	
Resolution	0.2° 300°C/ s
Zoom	0.2° 180°/s
Power	DC 12V
View	360° 0° 90°
Zoom	0.2° 180°/s
Resolution	128
View	90° 180°
Zoom	355° 4
Zoom	4 180°
Zoom	4 & ;
Remote	RS485
RS485	2400/4800/9600/19200 BPS
ID	1-254
Power	6W
Temp	-10°C +50°C/ -40°C +60°C & ;
Zoom	0.2° 180°/s
Zoom	1.8
CAM	

CCD	1/3" CCD 322 CMOS CCD+ SONY4191 ISP
	1920 * 1080
FOV	1 X10 CCD F = 5.1mm 51mm
FOV	APPR 55.2° H 3.2° V
CCD Size	CCD 0.5" BW 0.1LUX
S / N	52dB
IR	IR
ICR	ICR/IR
DNR	DNR / DNR / DNR / DNR
HLC	HLC / HLC
CCD Size	CCD
IRIS	IRIS
FLIP	FLIP ON / OFF

● PRODUCT PICTURE



● FACTORY & OFFICE

M TEAM



● EXHIBITIONS

M TEAM



████████ AHD ██████████