

# Bester HD H.265 4MP höchsten Auflösung Überwachungskamera (MVT-M3592)

## ● FEATURES



- Nimmt 4.0Megapixel Progressive Scan CMOS-Sensor mit Low Illumination.
- Unterstützt Networked Video von H.264 HP H.265 4MP @15fps 3MP @25fps Auflösung.
- **VandalProof**, durch Metallgehäuse gemacht
- Built-in: 3.6mm-Megapixel-Linse, POE und DC12V, Audio in / out, Nachtsicht 20 Meter.
- Standard-RTSP-und Flash-Video-Unterstützung, Unterstützung Internet Explorer, Firefox, Safari, Chrome, Opera etc.
- Support Two Way Sprechen zwischen Kamera mit Remote-PC oder Handy über das Internet.
- Android und IOS P2P Free App, kostenloses CMS.
- Kundenspezifische Voll Besondere ONVIF Version mit Gut Competibility mit Main Stream 3. CMS und NVRs

## ● SPECS



### Full HD, Networked

- Hochleistungs-DSP mit H.265 Videokompression-Code.
- Optimierte Intelligente Codierungsalgorithmus für Mehr Clear Video mit geringerer Bandbreite.

### Trusted Qualität

- Full Metal Shell, Präzisionsdesign, vandalensichere Gehäuse-Entwurf.
- Beleuchtung Prottech mit 6kV, Elektro von 8 kV mit Leistungsaufnahme Schutz.

### Volle Funktionalität

- Patentiertes Gehäusedesign Gut zu Consisitent und einfach für DIY Decken- und Wandmontage halten.
- Audio und Video Surveillance Mixed Stützen.
- Bilit-in IEEE802.3af POE.

|                 |                           |                                                                                                                                                 |
|-----------------|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Features</b> |                           | POE, Audio In/Out Cable, Powerful IR, DC12V, ONVIF 2.4, Free CMS, P2P Mobile and PC Remote Access                                               |
| <b>Cameras</b>  | Solution                  | Hi3516D+OV4689                                                                                                                                  |
|                 | Sensor                    | 1/3" CMOS                                                                                                                                       |
|                 | Min. Illumination (Color) | 0.01Lux/F1.2                                                                                                                                    |
|                 | Shutter                   | 1/5s-1/50,000s                                                                                                                                  |
|                 | Day&Night                 | IR-CUT Auto, Black, Color                                                                                                                       |
|                 | Images Settings           | Images, D&N Mode, Automatic Iris, Metering, White Balance, Exposure, Shutter, Mirror, Noise                                                     |
| <b>Codec</b>    | Video Resolution          | 4.0M(2592*1520)@15FPS, 3M@25FPS                                                                                                                 |
|                 | Codec                     | H.265                                                                                                                                           |
|                 | Video Frames              | Real Time, Max 25fps                                                                                                                            |
|                 | Codec Mode                | VBR/CBR                                                                                                                                         |
|                 | Data Rate                 | Three Streams, Main: 1500kbps-8Mbps<br>Sub: 50-1000kbps                                                                                         |
|                 | Frames                    | 1-30 frame adjustable                                                                                                                           |
|                 | Record                    | Video and Audio Recording and Playback, MP4 Format                                                                                              |
| <b>Network</b>  | Internet                  | QR Scan for Remote Surveillance, Free P2P, No Port Forwarding Needed. Free DDNS                                                                 |
|                 | Network Video             | Standard RTSP, FLASH                                                                                                                            |
|                 | Remote Access             | QR Scan Free APP (iphone/Andriod Smartphone), WEB (IE/Safari/Chrome/Firefox/Opera), NVR, CMS                                                    |
|                 | Compatibility             | Onvif 2.4 and latest version, Customized compatibility with main stream CMS and NVRs                                                            |
|                 | WIFI                      | NO                                                                                                                                              |
|                 | POE                       | Inside, IEEE802.3af                                                                                                                             |
|                 | Network Protocol          | P2P, RTP, RTSP, TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP                                                                                 |
| <b>Advanced</b> | System                    | Time Sync.<br>(Auto/Mannual/NTP/PC/NVR/RTC)<br>Online upgrade /Alarm /System Status Reports                                                     |
|                 | Audio&Video               | Audio (G.711A/U) / Video (Three Streams) / Video Mask / Motion Detection                                                                        |
|                 | Storage                   | NVR, Cloud                                                                                                                                      |
|                 | Events/Security/Log       | Events (Events Setting/Schedule Recording/Schedule FTP and Snapshot), Security (Filter of User and IP Address), Log (System/Alarm/Acceess etc.) |
| <b>Hardware</b> | Network Interfaces        | RJ-45, 10/100Base-T                                                                                                                             |
|                 | Microphone                | NO                                                                                                                                              |
|                 | Audio via Cable           | Audio In/Out, Talkback (G.711A, G.711U)                                                                                                         |
|                 | Local Storage             | NO                                                                                                                                              |
|                 | Others                    | NO                                                                                                                                              |
|                 | Application               | Indoor and Outdoor                                                                                                                              |
|                 | Installation              | Wall-mounting, Ceiling-mounting                                                                                                                 |
|                 | Accessories               | CD: 01.User Manual ; 02.CMS and User Manual; 03.IPCManager Tool and User Manual.                                                                |
|                 |                           | Others: Printed Quick-Start, Installation Location Lable, Installation Kits .                                                                   |
|                 | Power Supply              | DC12V & POE                                                                                                                                     |
|                 | Work Temperature          | -10°C-50°C                                                                                                                                      |
|                 | Work Humidity             | 10%-90%                                                                                                                                         |
|                 | Power Consumption         | 2 Watt                                                                                                                                          |

## Produkt-Abbildungen



Metal Housing



12 pcs Led IR  
Distance 10m



Vandalproof

M TEAM

## ● FACTORY & OFFICE

M' TEAM



## ● EXHIBITIONS

M' TEAM

