Comprar productos chinos en línea H.265 4MP 2592 * 1520 cámara IP domo (MVT-M2992)

FEATURES

- Adopta el sensor de CMOS de exploración progresiva de 4.0 megapíxeles con baja iluminación.
- Soporta vídeo en red de H.264 HP H.265 4MP @15fps, 3MP @25fps Resolución.
- Vándalo completoProof Dome (Caja de metal)
- Incorporado: 2.8 ~ lente megapixel de 12m m, POE y DC12V, entrada / salida de audio, visión nocturna de 30 metros.
- Compatible con RTSP y FLASH estándar, admite Internet Explorer, Firefox, Safari, Chrome, Opera, etc.
- Apoyo de dos vías hablando entre la cámara con PC remoto o teléfono móvil a través de Internet.
- Android y IOS P2P aplicación gratuita, CMS gratis.
- Customized Full ONVIF versión con buena competitividad con la corriente principal 3 ª CMS y NVRs

SPECS

Full HD, en red

- DSP de alto rendimiento utilizando el código de compresión de vídeo H.265.
- Algoritmo de codificación inteligente optimizado para un vídeo más claro con menor ancho de banda.

Calidad confiable

- Shell de Metal Completo, Diseño de Precisión, Diseño de Vivienda a Prueba de Vandalismo.
- Iluminación Prottech con 6Kv, electrostática de 8Kv con protección de entrada de potencia.

Funcionalidad completa

- Diseño de la cubierta de la bóveda, bueno mantener consisitent y fácil para la instalación del techo y de la pared de DIY.
- Audio y video Vigilancia mezclada apoyada.
- Bilit-in IEEE802.3af POE.

Features		POE, Audio In/Out Cable, Powerful IR, DC12V, ONVIF 2.4, Free CMS, P2P Mobile and PC Remote Access
Cameras	Solution	Hi3516D+OV4689
	Sensor	1/3" CMOS
	Min. Illumination (Color)	0.01Lux/F1.2
	Shutter	1/5s-1/50,000s
	Day&Night	IR-CUT Auto, Black, Color
	Images Settings	Images, D&N Mode, Automatic Iris, Metering, White Balance, Exposure, Shutter, Mirror, Noise
Codec	Video Resolution	4.0M(2592*1520)@15FPS, 3M@25FPS
	Codec	H..265
	Video Frames	Real Time, Max. 25fps
	Codec Mode	VBR/CBR
	Data Rate	Three Streams, Main: 1500kbps-8Mbps Sub: 50-1000kbps
	Frames	1-30 frame adjustable
	Record	Video and Audio Recording and Playback, MP4 Format
Network	Internet	QR Scan for Remote Surveillance, Free P2P, No Port Forwarding Needed. Free DDNS
	Network Video	Standard RTSP, FLASH
	Remote Access	QR Scan Free APP (iphone/Andriod Smartphone), WEB (IE/Safari/Chrome/Firefox/Opera), NVR, CMS
	Compatibility	Onvif 2.4 and latest version, Customized compatibility with main stream CMS and NVRs
	WIFI	NO
	POE	Inside, IEEE802.3af
	Network Protocol	P2P,RTP,RTSP,TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP
Advanced	System	Time Sync. (Auto/Mannual//NTP/PC/NVR/RTC) Online upgrade /Alarm /System Status Reports
	Audio&Video	Audio (G.711A/U) / Video (Three Streams) / Video Mask / Motion Detection
	Storage	NVR, Cloud
	Events/Security/Log	Events (Events Setting/Schedule Recording/Schedule FTP and Snapshot), Security (Filter of User and IP Address), Log (System/Alarm/Acceess etc.)
Hardware	Network Interfaces	RJ-45, 10/100Base-T
	Microphone	NO
	Audio via Cable	Audio In/Out, Talkback (G.711A, G.711U)
	Local Storage	NO
	Others	NO
	Application	Indoor and Outdoor
	Installation	Wall-mounting, Ceiling-mounting
	Accessories	CD: 01.User Manual ; 02.CMS and User Manual; 03.IPCManager Tool and User Manual.
		Others: Printed Quick-Start, Installation Location Lable, Installation Kits.
	Power Supply	DC12V & POE
	Work Temperature	-10℃-50℃
	Work Humidity	10%-90%
	Power Consumption	2 Watt

MVTEAM

FACTORY & OFFICE

EXHIBITIONS