

Cámara Ethernet H.265 4MP Video Monitoring IP System (MVT-M2892)

● FEATURES



- Adopta el sensor CMOS de escaneo progresivo 4.0Megapixel con baja iluminación.
- Admite video en red de H.264 HP H.265 4MP @15fps, 3MP @25Resolución de fps.
- **Vandalismo completo** Domo de prueba (caja de metal)
- Incorporado: lente CS de 3 mm megapíxeles 6 mm, POE y DC12V, entrada / salida de audio, visión nocturna a 30 metros.
- Soporte estándar de RTSP y FLASH Video, soporte para Internet Explorer, Firefox, Safari, Chrome, Opera, etc.
- Compatible con Two Way Speaking entre la cámara con una PC remota o un teléfono móvil a través de Internet.
- Aplicación gratuita Android e IOS P2P, CMS gratis.
- Versión completa personalizada de ONVIF con buena competencia con Main Stream 3rd CMS y NVR

● SPECS



Full HD, en red

- DSP de alto rendimiento que utiliza el código de compresión de video H.265.
- Algoritmo de codificación inteligente optimizado para video más claro con menor ancho de banda.

Calidad confiable

- Full Metal Shell, diseño de precisión, diseño de vivienda a prueba de vandalismo.
- Iluminación Prottech con 6Kv, electrostática de 8Kv con protección de entrada de energía.

Funcionalidad completa

- Diseño de la carcasa del domo, bueno para mantener constante y fácil para la instalación de techos y paredes de bricolaje.
- Audio y video Vigilancia mixta compatible.
- Bilit-in IEEE802.3af POE.

| | | |
|-------------------|---------------------------|---|
| Features | | POE, Audio In/Out Cable, Powerful IR, DC12V, ONVIF 2.4, Free CMS, P2P Mobile and PC Remote Access |
| Cameras | Solution | Hi3516D+OV4689 |
| | Sensor | 1/3" CMOS |
| | Min. Illumination (Color) | 0.01Lux/F1.2 |
| | Shutter | 1/5s-1/50,000s |
| | Day&Night | IR-CUT Auto, Black, Color |
| | Images Settings | Images, D&N Mode, Automatic Iris, Metering, White Balance, Exposure, Shutter, Mirror, Noise |
| Codec | Video Resolution | 4.0M(2592*1520)@15FPS, 3M@25FPS |
| | Codec | H.265 |
| | Video Frames | Real Time, Max 25fps |
| | Codec Mode | VBR/CBR |
| | Data Rate | Three Streams, Main: 1500kbps-8Mbps Sub: 50-1000kbps |
| | Frames | 1-30 frame adjustable |
| | Record | Video and Audio Recording and Playback, MP4 Format |
| Network | Internet | QR Scan for Remote Surveillance, Free P2P, No Port Forwarding Needed. Free DDNS |
| | Network Video | Standard RTSP, FLASH |
| | Remote Access | QR Scan Free APP (iphone/Andriod Smartphone), WEB (IE/Safari/Chrome/Firefox/Opera), NVR, CMS |
| | Compatibility | Onvif 2.4 and latest version, Customized compatibility with main stream CMS and NVRs |
| | WIFI | NO |
| | POE | Inside, IEEE802.3af |
| | Network Protocol | P2P,RTP,RTSP,TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP |
| Advanced | System | Time Sync. (Auto/Mannual/NTP/PC/NVR/RTC) Online upgrade /Alarm /System Status Reports |
| | Audio&Video | Audio (G.711A/U) / Video (Three Streams) / Video Mask / Motion Detection |
| | Storage | NVR, Cloud |
| | Events/Security/Log | Events (Events Setting/Schedule Recording/Schedule FTP and Snapshot), Security (Filter of User and IP Address), Log (System/Alarm/Access etc.) |
| Hardware | Network Interfaces | RJ-45, 10/100Base-T |
| | Microphone | NO |
| | Audio via Cable | Audio In/Out, Talkback (G.711A, G.711U) |
| | Local Storage | NO |
| | Others | NO |
| | Application | Indoor and Outdoor |
| | Installation | Wall-mounting, Ceiling-mounting |
| | Accessories | CD: 01.User Manual ; 02.CMS and User Manual; 03.IPCManager Tool and User Manual. Others: Printed Quick-Start, Installation Location Lable, Installation Kits . |
| | Power Supply | DC12V & POE |
| | Work Temperature | -10°C-50°C |
| | Work Humidity | 10%-90% |
| Power Consumption | 2 Watt | |

● FACTORY & OFFICE

M'TEAM



● EXHIBITIONS

M'TEAM

