

Meilleur HD H.265 4MP plus haute caméra de surveillance de la résolution (MVT-M3592)

● FEATURES



- Adopte 4.0Megapixel Progressive Scan capteur CMOS avec faible éclairage.
- Prise en charge réseau vidéo H.264 HP H.265 4MP @15fps @ 3MP25fps Résolution.
- **Vandale**Preuve, faite par boîtier métallique
- Built-in: 3.6mm lentille mégapixels, POE et DC12V, audio in / out, vision nocturne 20 mètres.
- Standard RTSP et Flash Vidéo pris en charge, de soutien Internet Explorer, Firefox, Safari, Chrome, Opera, etc.
- Soutien Two Way Parlant entre la caméra avec un PC ou un téléphone mobile à distance via Internet.
- Android et IOS App P2P gratuit, CMS gratuit.
- Personnalisé Version complète ONVIF avec Good Competibility avec Main Stream 3ème CMS et NVR

● SPECS



Full HD, en réseau

- DSP de haute performance utilisant H.265 Video Code de compression.
- Optimisé algorithme de codage intelligent pour Plus Clear Video avec la Basse bande passante.

Trusted Qualité

- Full Metal Shell, Precision design, conception de logements anti-vandalisme.
- Éclairage Prottech avec 6kv, électrostatiques de 8kV avec protection d'entrée d'alimentation.

Fonctionnalité complète

- Brevetés conception de logements, bon de garder Consistent et facile pour plafond bricolage et l'installation mur.
- Surveillance audio et vidéo pris en charge mixte.
- Bilit en IEEE802.3af POE.

Features		POE, Audio In/Out Cable, Powerful IR, DC12V, ONVIF 2.4, Free CMS, P2P Mobile and PC Remote Access
Cameras	Solution	Hi3516D+OV4689
	Sensor	1/3" CMOS
	Min. Illumination (Color)	0.01Lux/F1.2
	Shutter	1/5s-1/50,000s
	Day&Night	IR-CUT Auto, Black, Color
	Images Settings	Images, D&N Mode, Automatic Iris, Metering, White Balance, Exposure, Shutter, Mirror, Noise
Codec	Video Resolution	4.0M(2592*1520)@15FPS, 3M@25FPS
	Codec	H.265
	Video Frames	Real Time, Max 25fps
	Codec Mode	VBR/CBR
	Data Rate	Three Streams, Main: 1500kbps-8Mbps Sub: 50-1000kbps
	Frames	1-30 frame adjustable
	Record	Video and Audio Recording and Playback, MP4 Format
Network	Internet	QR Scan for Remote Surveillance, Free P2P, No Port Forwarding Needed. Free DDNS
	Network Video	Standard RTSP, FLASH
	Remote Access	QR Scan Free APP (iphone/Andriod Smartphone), WEB (IE/Safari/Chrome/Firefox/Opera), NVR, CMS
	Compatibility	Onvif 2.4 and latest version, Customized compatibility with main stream CMS and NVRs
	WIFI	NO
	POE	Inside, IEEE802.3af
	Network Protocol	P2P, RTP, RTSP, TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP
Advanced	System	Time Sync. (Auto/Mannual/NTP/PC/NVR/RTC) Online upgrade /Alarm /System Status Reports
	Audio&Video	Audio (G.711A/U) / Video (Three Streams) / Video Mask / Motion Detection
	Storage	NVR, Cloud
	Events/Security/Log	Events (Events Setting/Schedule Recording/Schedule FTP and Snapshot), Security (Filter of User and IP Address), Log (System/Alarm/Acceess etc.)
Hardware	Network Interfaces	RJ-45, 10/100Base-T
	Microphone	NO
	Audio via Cable	Audio In/Out, Talkback (G.711A, G.711U)
	Local Storage	NO
	Others	NO
	Application	Indoor and Outdoor
	Installation	Wall-mounting, Ceiling-mounting
	Accessories	CD: 01.User Manual ; 02.CMS and User Manual; 03.IPCManager Tool and User Manual. Others: Printed Quick-Start, Installation Location Lable, Installation Kits .
	Power Supply	DC12V & POE
	Work Temperature	-10℃-50℃
	Work Humidity	10%-90%
	Power Consumption	2 Watt

Photos du produit



Metal Housing



12 pcs Led IR
Distance 10m



Vandalproof

M TEAM

● FACTORY & OFFICE

M' TEAM



● EXHIBITIONS

M' TEAM

