

## ● FEATURES



- 1) outdoor IP66
- 2) 128 presets, 4 tour, 4 scan, 4 patterns
- 3) Built-in OSD display menu
- 4) Lightningproof design, provide subtle Lightning Protection

## ● SPECS



Model No.	All-in-one Camera	Specification
MVT-MO705	1/3 inch, SONY238 CMOS 18X 1000TVL	<ul style="list-style-type: none"> <li>• outdoor IP66, 6" speed dome camera</li> <li>• Pan continuously 360° rotate, tilt 90° rotation with auto-flip</li> <li>• Pan speed: 300°/s(max), Tilt speed: 120°/s(max)</li> <li>• Built-in OSD display menu</li> <li>• 128 presets, 4 tour, 4 scan, 4 patterns, 8 programmable zones with editable title, preset precision degree 0.01°</li> <li>• Support Software and hardware address set, built-in multi-protocols</li> <li>• Lightningproof design, provide subtle Lightning Protection</li> </ul>
MVT-MO701	1/4 inch, Effio-E CCD 22X 650TVL	
MVT-MO702	Samsung Samsung SCM-2270 27X 1/4 inch CCD, 600TVL	
MVT-MO703	Samsung SCM-3371 37X 1/4 inch CCD WDR, 600TVL	
MVT-MO704	Sony 36X FCB1010(3.5-129mm)WDR, 530TVL	



● EXHIBITIONS

