

2MP Outdoor Hybrid AHD TVI CVI Analog 4.2" Mini PTZ Camera

● FEATURES



- *Solution:NVP2441H+IMX323,1080P
- *5.1-51mm 10X zoom lens,ICR
- *4.2" Outdoor Mini PTZ Camera
- *Without IR leds
- *Day/Night(ICR)
- *0.1°-200 °pan speed & 0.1°- 180°/s tilt speed,90°tilt auto flip
- *128 presets,4 auto scans,4 tours,4 patterns
- *Clock function
- *With OSD menu,AHD UTC/RS485 remote controlling
- *Pelco-P/D (Auto recognition)
- * lightning-proof, surge-proof, IP66
- *Working Temperature: -20°C □ +60°C
- *DC12V/1.5A power supply

● SPECS



PTZ Specs	
Manual speed	Pan□0.2°□300°/s□
	Tilt□0.2°□180°/s□
Power supply	DC 12V/1.5A
Rotation	Pan continuously 360°, tilt 0□90° with auto-flip
Speed Proportion	As the length of focus, to auto-adjust the speed
Preset	128 preset, title can be edited
Auto-flip	Tilt down 90°, with auto-flip 180°
Scan	355°programmable, 4 scan
Pattern	4 patterns, and each record time is not less than 180s
Tour	4 tour, and speed & park time of presets can be set.
Remote controlling	RS485
Baud rate (RS485)	2400□4800□9600/19200 bps
ID range	1-254
Power consumption	6W
Temperature	-10°C□+50°C/ -40°C□+60°C via heater & Fans (Optional)
Installation	Wall installation, ceiling installation

Net weight	1.8Kg
CAM Specs	
Sensor	NVP2441H+IMX323
	1080P 1920*1080
OPTICS	Optical x10,Zoom f = 5.1mm ~ 51mm
Angle	Appr. 55.2°(Wide) to 3.2°(Tele)
Min. Illumination	Color : 0.5 lux , BW : 0.1lux
S/N (Y signal)	52dB
White Balance	Auto
ICR	Manual/Auto
DNR	Auto / Off / Low / Middle / High
HLC	Off / On
Max Gain	Auto
IRIS	Auto
FLIP	Vertical , Horizontal ,Vertical-Horizontal,OFF Selectable

● **PRODUCT PICTURE**

M TEAM



● FACTORY & OFFICE

M' TEAM



● EXHIBITIONS

M' TEAM

