

Feature

- 4*1080P(NVR), 4*720P(AHD), 4*960H(Analog DVR) 3 ModesHybrid AHD DVR-NVR-Analog DVR
- standard HD HDMI/VGA interface
- Support HD video signal recording, storage, playback and transport
- Low latency system in favour of real-time HDvideo image processing

Specification

Model		MVT-AH6404H
Compression		H.264 Standard compression
Operation		Embedded Linux
Image coding-control		Image edit adjustable,both changable and fix stream optional
Dual stream		Can be set up in each channel
Monitor image quality		4*1080P(NVR),4*720P(AHD),4*960H(Analog DVR)
Image dynamic detection		Multiple detection areas in each channel
Video framerate		720P 25FPS/CH AHD, 1080P 25FPS/CH NVR, 960H 25FPS/CH Analog DVR
Image playback quality		AHD 4*720P 50FPS ,NVR 4*1080P 50FPS, Analog DVR 4*960H 100FPS
Video mode		Support manual, automatic, dynamic monitoring, alarm trigger video mode
Backup mode		U disk, USB portable disk, USB burn, Network storage and backup
Operate mode		Mouse, Remote controller,Front Panel Control
login locally		admin and password
Save recording		local hard disk and network
External interface	Video input	720P 25FPS/CH AHD, 1080P 25FPS/CH NVR, 960H 25FPS/CH Analog DVR
	Audio input	4×RCA
	Video output	1*VGA,1*HDMI
	Audio output	1*RCA,1*HDMI
	Network interface	10M/100M base-T Ethernet (RJ-45)
	USB connect port	2 x USB 2.0
	RS485	RS485*1
	Alarm input	NO
	Alarm output	NO
Hard disk	Internal HDD	2 SATA HDD port
	Maximum capacity	Maximum 4TB each SATA□
Cell phone monitoring		Support Window Mobile, iPhone,iPad, Android
Power		12V/4A
DVR size		335*255*50mm
Weight		<3.2kg(without HDD)



P2P Function Advantages:

- *No stable IP address needed
- *No DDNS setup needed
- *No Router setup needed
- *Reducing your after-sales cost

Mobile Phone View

(All MVTEAM DVR, AHD DVR, CVI DVR, SDI DVR, NVR support)



Achieve Monitoring All kinds of Cameras in One Screen on Computer



● FACTORY & OFFICE

M TEAM



● EXHIBITIONS

M TEAM

