

Main Features:

1. Economical Security camera
2. Nice image quality and cheap price
3. widely compatible, able to match AHD DVR and All Standalone DVR
4. Easy to operate, Plug and Play
5. Advanced CMS software supporting 3G remote view

Application Places

Apply to the financial, supermarket, telecommunications, government, schools, airports, factories, hotels, museums and other places of requirement of high-definition.

Model	MVT-D4341O	MVT-D4341Z	MVT-D4351E
Active Pixel	P: 720(H)×576(V) N: 720(H)×487(V)	728*488	P: 976*582 N: 976*494
Resolution	600TVL	700TVL	700TVL
Video Out	1.0Vp-p Composite Signal (75ohm)	1.0Vp-p Composite Signal (75ohm)	1.0Vp-p Composite Signal (75ohm)
SYNC		Internal	
Sensor	PC7030	PC3089	P: ICX811AK N: ICX810AK
Minimum Illumination	0.01Lux	0.01Lux	0.05Lux
Gama adjust	0.45	0.45	0.45
Electric Shutter	PAL:1/50s-1/100000s NTSC:1/60s-1/100000s	PAL:1/50s-1/100000s NTSC:1/60s-1/100000s	PAL:1/50s-1/100000s NTSC:1/60s-1/100000s
S/N Ratio	48dB(min)(AGC closed)	48dB(min)(AGC closed)	48dB(min)(AGC closed)
DNR	-	-	2D-DNR
AWB	AUTO	AUTO	ATW/PUSH/USER1/ USER2/ANTI CR/ MANUAL/PUSH LOCK
AGC	AUTO	AUTO	AUTO
BLC	-	-	ON/OFF
OSD	-	-	YES
D-WDR	-	-	LOW/MID/HIGH
SWDR	-	-	-
HLC	-	-	ON/OFF
D-Zoom	-	-	-
IR-Smart	-	-	ON/OFF
Day/Night	-	-	Auto□Color□ B/W□Ext1□Ext2
Motion Detection	-	-	4 areas optional
Language	-	-	8 kinds

Power	50mA	50mA	80mA
Dissipation			
Power Input	DC12V±1V	DC12V±1V	DC12V±1V
Operation	Temperature -10°C~+60°C,Humidity	Temperature -10°C~+60°C,Humidity	Temperature -10°C~+60°C,Humidity
Temperature	less than 85%RH	less than 85%RH	less than 85%RH

● PRODUCT PICTURE

M TEAM



● FACTORY & OFFICE

M TEAM



