

**Main Features:**

1. Economical Security camera
2. Nice image quality and cheap price
3. widely compatible, able to match AHD DVR and All Standalone DVR
4. Easy to operate, Plug and Play
5. Advanced CMS software supporting 3G remote view

**Application Places**

Apply to the financial, supermarket, telecommunications, government, schools, airports, factories, hot els, museums and other places of requirement of high-definition.

Model	MVT-R11410	MVT-R1141N	MVT-R1151E
Active Pixel	P: 720(H)×576(V) N: 720(H)×487(V)	728*488	P: 976*582 N: 976*494
Resolution	600TVL	900TVL	700TVL
Video Out	1.0Vp-p Composite Signal (75ohm)	1.0Vp-p Composite Signal (75ohm)	1.0Vp-p Composite Signal (75ohm)
SYNC		Internal	
Sensor	PC7030	PC1099	P: ICX811AK N: ICX810AK
Minimum Illumination	0.01Lux	0.01Lux	0.05Lux
Gama adjust	0.45	0.45	0.45
Electric Shutter	PAL:1/50s-1/100000s NTSC:1/60s-1/100000s	PAL:1/50s-1/100000s NTSC:1/60s-1/100000s	PAL:1/50s-1/100000s NTSC:1/60s-1/100000s
S/N Ratio	48dB(min)(AGC closed)	48dB(min)(AGC closed)	48dB(min)(AGC closed)
DNR	-	-	2D-DNR
AWB	AUTO	AUTO	ATW/PUSH/USER1/ USER2/ANTI CR/ MANUAL/PUSH LOCK
AGC	AUTO	AUTO	AUTO
BLC	-	-	ON/OFF
OSD	-	-	YES
D-WDR	-	-	LOW/MID/HIGH
SWDR	-	-	-
HLC	-	-	ON/OFF
D-Zoom	-	-	-
IR-Smart	-	-	ON/OFF
Day/Night	-	-	Auto[]Color[] B/W[]Ext1[]Ext2
Motion Detection	-	-	4 areas optional
Language	-	-	8 kinds

Power  
Dissipation  
Power Input  
Operation  
Temperature

50mA  
DC12V±1V  
Temperature -10°C~+60°C, Humidity  
less than 85%RH

50mA  
DC12V±1V  
Temperature -10°C~+60°C, Humidity  
less than 85%RH

80mA  
DC12V±1V  
Temperature -10°C~+60°C, Humidity  
less than 85%RH

## ● PRODUCT PICTURE

**M TEAM**



## ● FACTORY & OFFICE

**M TEAM**



● EXHIBITIONS

