

- 1.support P2P function via IE, QMEYE CMS in PC and iPhone & Andriod mobile phone.
- 2.QMEYE software can support record the video in mobile phone and remote playback the recorded video in DVR
- 3.One Client Software can manage mutiple security cameras
- 4.Support Soft update, Support 20 Languages

Model	MVT-6008	
System	Main Processor	HISILICON
	System Resource	Pentaplex: Live recording, Playback, Backup, Remote access, PTZ control, Mobile monitoring
	Control Mode	USB mouse, IR remote, Keyboard, Network
Video	Input	8×BNC,(1.0Vp-p,75Ω)
	Standard	D1□NTSC 120F/S,PAL100F/S
	Output	1×BNC,(1.0Vp-p,75Ω),1×VGA
Audio	Input	8×RCA
	Output	1×BNC
Display	Display Split	1/4/8/9
	Resolution	VGA:1280*1024, 1024*768, 800*600
	Tour Display	Support
Recording	OSD	Camera title, Time, Video loss, Motion detection, Recording
	Video/Audio	H.264/ADPCM
	Image Resolution	D1(720*576/720*480), HD1(720*288/720*240), CIF(352*288/352*240)
	Encoding stream	Main stream D1:120FPS; CIF: 240FPS
		Extra CIF:60FPS
	Recording Mode	Manual, schedule,Motion detection, Alarm
	Recording Priority	Manual>Alarm>Motion detection

Video detection & Alarm	Trigger events	Recording, PTZ movement, Alarm, E-mail
	Motion detection	Zones:396□22*18□,Sensitivity:1-5□Level 5 is the highest□
	Video loss	Support
	Alarm	4 IN /1OUT
	Playback channel	8CH
Playback & Backup	Playback speed	D1□60FPS;CIF:240FPS
	Search mode	Time, Alarm, Motion detection
	Playback function	Play, Pause, Stop, Fast forward, Slow forward, Full screen etc. Recording files can be viewed by dragging the progress bar back and forth
	Backup mode	U-disk/ USB-HDD/USB- CD/DVD-RW/Network
Network	Physical interface	RJ-45port(10/100M)
	Network function	TCP/IP,UDP,DHCP,DNS,IP filter, PPPOE, E-mail, Alarm server, UPNP, DDNS,DNS Binding
	Remote operation	Monitor, PTZ control, Playback, System setting, files download, Log information
	Mobile Phone	Support Window Mobile, Symbian, Android, iPhone, Blackberry etc.
Hard Disk	Hard disk	1 SATA port, the capacity of single hard disk MAX 2T
	Space occupation	Audio: 14.4MB/H, Video: 56-900MB/H
	HDD management	Hard disk hibernation technology, HDD faulty alarm, file restoration
Auxiliary Interface	USB	Two USB2.0 interface, for connecting mouse, U-disk, USB hard disk
	RS485	PTZ control
	Power supply	12V/3A
Environment	Working environment	-10℃~+55℃/10~90%RH/86~106Kpa
	Dimension	335*250*50mm(Product size)
	Weight	2.6 kg(W/O HDD)



P2P Function Advantages:


- *No stable IP address needed**
- *No DDNS setup needed**
- *No Router setup needed**
- *Reducing your after-sales cost**

Mobile Phone View

(All MVTEAM DVR, AHD DVR, CVI DVR, SDI DVR, NVR support)



Achieve Monitoring All kinds of Cameras in One Screen on Computer



● FACTORY & OFFICE

M TEAM



● EXHIBITIONS

M TEAM

