

## Custom-made Logo 4MP 3MP Bullet POE IP Camera with Vari-focal Lens(MVT-M1892)

### ● FEATURES

M'TEAM

Adopt infrared antireflection panel design, make the camera with better night vision.

Infrared Antireflection Panel



Quality reflective overlay, surface-emitting technology, can magnify the effect of focus, improve product performance and reliability.



HD 3MP 2.8-12mm vari-focal lens(M12 Mount),bring more clear image.



### Adjustable Bracket



### Size



IP66 Waterproof Grade,give you more reliable protection



● SPECS



- Adopts 4.0Megapixel Progressive Scan CMOS Sensor with Low Illumination.
- Supports Networked Video of H.264 HP 4MP@15fps 3MP@25fps Resolution.
- IP66,WaterProof
- Built-in: 6mm megapixel lens, POE and DC12V, Audio in/out, Night Vision 30 meters.
- Standard RTSP and FLASH Video Supported,Support Internet Explorer, Firefox, Safari, Chrome, Opera etc
- Support Two Way Speaking between Camera with Remote PC or Mobile Phone through Internet.
- Customized Full Featured ONVIF Version with Good Competibility with Main Stream 3rd CMS and NVR S

Applications:

Finance, supermarkets, telecommunications, government, schools, airports, factories, hotels, museums and other places to apply the high-resolution requirements.

|          |   |
|----------|---|
| Model    | MVT-M1892   |
| Features | POE, Audio In/Out Cable, Powerful IR, DC12V, ONVIF 2.4, Free CMS, |
|          | P2P Mobile and PC Remote Access                                   |

|          |                           |   |
|----------|---------------------------|---|
| Cameras  | Solution                  | Hi3516D+OV4689  |
|          | Sensor                    | 1/3" CMOS   |
|          | Min. Illumination (Color) | 0.01Lux/F1.2  |
|          | Shutter                   | 1/5s-1/50,000s  |
|          | Day&Night                 | IR-CUT Auto, Black, Color   |
|          | Images Settings           | Images, D&N Mode, Automatic Iris, Metering, White Balance, Exposure, Shutter, Mirror, Noise |
| Codec    | Video Resolution          | 4MP(2592*1520)@15FPS, 3MP(2048*1520)@25FPS  |
|          | Codec                     | H.264 HP, H.265   |
|          | Video Frames              | Real Time, Max. 25fps   |
|          | Codec Mode                | VBR/CBR   |
|          | Data Rate                 | Three Streams, Main: 1500kbps-8Mbps Sub: 50-1000kbps  |
|          | Frames                    | 1-30 frame adjustable   |
|          | Record                    | Video and Audio Recording and Playback, MP4 Format  |
| Network  | Internet                  | QR Scan for Remote Surveillance, Free P2P, No Port Forwarding Needed. Free DDNS             |
|          | Network Video             | Standard RTSP, FLASH  |
|          | Remote Access             | QR Scan Free APP (iphone/Andriod Smartphone), WEB (IE/Safari/Chrome/Firefox/Opera),         |
|          | □                         | NVR, CMS  |
|          | Compatibility             | Onvif 2.4 and latest version, Customized compatibility with main stream CMS and NVRs        |
|          | WIFI                      | NO  |
|          | POE                       | Inside, IEEE802.3af   |
|          | Network Protocol          | P2P,RTP,RTSP,TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP                                      |
| Advanced | System                    | Time Sync. (Auto/Manual//NTP/PC/NVR/RTC) Online upgrade /Alarm /System Status Reports       |
|          | Audio&Video               | Audio (G.711A/U) / Video (Three Streams) / Video Mask / Motion Detection                    |
|          | Storage                   | NVR, Cloud  |
|          | Events/Security/Log       | Events (Events Setting/Schedule Recording/Schedule FTP and Snapshot),                       |
|          | □                         | Security (Filter of User and IP Address), Log (System/Alarm/Access etc.)                    |

|          |                    |  |
|----------|--------------------|--|
| Hardware | Network Interfaces | RJ-45, 10/100Base-T  |
|          | Microphone         | NO   |
|          | Audio via Cable    | Audio In/Out, Talkback (G.711A, G.711U)  |
|          | Local Storage      | NO   |
|          | Others             | NO   |
|          | Application        | Indoor and Outdoor   |
|          | Installation       | Wall-mounting, Ceiling-mounting  |
|          | Accessories        | CD: 01.User Manual ; 02.CMS and User Manual; 03.IPCManager Tool and User Manual. |
|          | □                  | Others: Printed Quick-Start, Installation Location Lable, Installation Kits.     |
|          | Power Supply       | DC12V & POE  |
|          | Work Temperature   | -10°C-50°C   |
|          | Work Humidity      | 10%-90%  |
|          | Power Consumption  | 2 Watt   |

▼ Packages
**M'TEAM**

Brand Camera Package



Neutral Camera Package



Brand DVR Package



Package: MVTEAM Brand Box Or Netural Box Or Specified by customer.

▼ Shipping
**M'TEAM**










Shipping: Based on the your demands to choose the best shipping way.

**Contact us:**

If you have any question, welcome to [Contact us](#).

Your close attention to our company is highly appreciated.

Welcome to visit our official website [www.myteamcctv.com](http://www.myteamcctv.com) to view video demos,download product catalog and read CCTV technical articles