



- 1 Built-in OSD menu, can change information and parameter of dome through menu, also can set and call presets, tour, scan, pattern, camera mode and display name etc.
- 2 Horizontal Speed $0.1^{\circ} \sim 220^{\circ}/s$, Vertical Speed $0.1^{\circ} \sim 180^{\circ}/s$
- 3 Screen display position of pan/tilt, zoom, temp inside, direction lable, time and date.
- 4 128 presets (titles can be set); Tour is based on presets, speed & park time of presets can be set.

- 5 Pan 360° continuously, tilt 90° rotation, auto-flip, manual speed: 0.4°/320°/s.
- 6 4 pattern, and each record time is not less than 180s.
- 7 4 scan, support scan between left and right limite at an appointed speed.
- 8 Auto scan function, and at the same time, dome can still zoom, and run tilt
- 9 Park action function, can auto-call presets or start-up tour, pattern and scan after dome id for a period of time
- 10 Communication (support Rs485).
- 11 Built-in multi-protocols and fully compatible with PELCO-D PELCO-P
- 12 IP66 all-day protection cover, built-in constant temperature device.
- 13 Built-in TVS4000V lightning-proof, surge-proof and wave-proof.

SPECS



PTZ Specs	
Manual speed	Pan 0.1°/300°/s
	Tilt 0.1°/220°/s
Preset speed	220°/s
Rotation	Pan continuously 360°, tilt 0°/90° with auto-flip
Speed Proportion	As the length of focus, to auto-adjust the speed
Preset	128 preset, title can be edited
Auto-flip	Tilt down 90°, with auto-flip 180°
Scan	355°programmable, 4 scan
Decoder	Built-in
Video output	Female BNC
Remote controlling	RS485
Baud rate (RS485)	2400/4800/9600/19200 bps
ID range	1/254
Temperature	Outdoor -10°C/+60°C
Humidity	0/95% non-condensation
Protection grade	IP66, lightning-proof, surge-proof, wave-proof, all-day defend cover
Power supply	AC 24V ±4V
Power consumption	Indoor 10W
Temperature	-10°C/+60°C
Gross weight	2.9kg
Cam Specs	
CMOS	1/3" Sony CMOS Sensor
	1305(H) × 1049(V) Approx. 1.37M pixels
OPTICS	Optical x20, f = 4.7 mm ~ 84.6.0 mm
Angle	Appr. 55.2°(Wide) to 3.2°(Tele)
Scanning System	Progressive Scan
Min. Illumination	Color : 0.5 lux , BW : 0.1lux
S/N (Y signal)	52dB
White Balance	Auto
ICR	Manual/Auto

DNR	Auto / Off / Low / Middle / High
HLC	Off / On
Defog	Off / On
Max Gain	Auto
IRIS	Auto
FLIP	Vertical , Horizontal ,Vertical-Horizontal,OFF Selectable

● FACTORY & OFFICE



● EXHIBITIONS



For more about AHD Products welcome to Visit [FAQ](#)