

HD CCTV Tester Monitor 5MP 4MP 3MP AHD TVI CVI Camera Video Tester with 5 inch LCD Screen

What Can You Do With a HD CCTV Tester?

- 1- HD TVI CVI AHD CVBS camera video test
- 2- CCTV camera audio test
- 3- Test and control PTZ Camera(RS485)
- 4- Connect DVR to show image thru HDIMI 1.0/VGA input
- 5- Network Cable Test
- 6- Power supply for CCTV Cameras
- 7- Charging for mobile phone
- 8- LED emergency lighting

MVTEAM www.mvteamcctv.com



● FEATURES

MVTEAM

- * 5 "TFT - LCD HD screen
- * Resolution: 800 * 480
- * Multi-language OSD menu
- * The display brightness/contrast/color saturation is adjustable
- * Power output: DC 12V/ 1A for AHD, TVI, CVI cameras;
DC 5V/1A power output for LED emergency lighting and mobile phone charging
- * Built-in 2600MAH lithium-ion battery
- * Support AHD\TVI(3MP,4MP, 5MP), CVI(3MP, 4MP) Cameras test based on coaxial cable
- * Support PTZ RS485 test
- * Advanced functions: HD Video Test; Display PAL/NTSC; Audio Test; Network Cable Test
- * Support HDMI 1.0 input, VGA input to connect DVR
- * Support BNC output

Video test	
Video System	NTSC/PAL(auto adapt)
Video level	1VPP
Display screen	5 inch LCD 800*480 resolution
Screen adjustment	Video display brightness, contrast, color saturation adjustable
Video input / output	HDMI 1.0/VGA/BNC input; 1ch BNC Output
Camera/VGA/HDMI Test	
SD signal Format	NTSC ,PAL
HD video signal	HD AHD, TVI, CVI, CVBS
Resolution	D1, 720P, 960P, 1080P, 3MP, 4MP, 5MP
VGA/HDMI test	Support VGA/HDMI 1.0 video input to connect DVR, maximum resolution reach to 1920x1080.
Power output	
Power output	DC 12V/1A for cameras USB1 DV 5V/1A
Audio test	
Audio test	Input audio signal, and played on the internal speaker
Power supply	
External power supply	DC 5V(1A)
Battery-powered	Built-in 18650 2600mAh battery X 2
Charge	Charge time 3-4 hours Battery power time 11 hours
Power saving features	Energy saving, battery capacity indicator
System settings	
Language settings	Chinese, English user selectable
Auto power off	Disable / 5-60 minutes
Cable test	
UTP Cable Tester	Display UTP Cable connection status, cable type and the sequence of wires as well as read the number of the test box.
PTZ Controller	RS485, compatible with protocols PELCO-D/P Baud Rate: 600, 1200, 2400, 4800, 9600, 14400bps
Working environment and Specifications	
Working Temperature	-10°C ~ +50°C
Working Humidity	30% ~90%

CCTV Tester



Buttons & Ports



Package & Accessories



● FACTORY & OFFICE

M' TEAM



● EXHIBITIONS

M' TEAM



Contact us:

If you have any question, welcome to [Contact us](#).

Your close attention to our company is highly appreciated.

Welcome to visit our official website www.mvteamcctv.com to view [video demos](#), [download product catalog](#) and read [CCTV technical articles](#).