

Main Features:

1. Economical Security camera
2. Nice image quality and cheap price
3. widely compatible, able to match AHD DVR and All Standalone DVR
4. Easy to operate, Plug and Play
5. Advanced CMS software supporting 3G remote view

Application Places

Apply to the financial, supermarket, telecommunications, government, schools, airports, factories, hotels, museums and other places of requirement of high-definition.

Model	MVT-R30410	MVT-R3041F	MVT-R3041Z	MVT-R3041E	MVT-R3041A	MVT-R3051E	MVT-R3051F
Image Sensor	1/4" Color CMOS	1/3" Color CMOS	1/3" Color CMOS	1/4" Color CMOS	1/3" Color CMOS	1/3 sony CCD	1/3 sony CCD
TV System	PAL/NTSC						
Image Resolution	PAL:752(H)×582(V), NTSC:768(H)×494(V)	PAL:752(H)×582(V), NTSC:768(H)×494(V)	PAL:976(H)×582(V), NTSC:976(H)×494(V)	PAL:976(H)×582(V), NTSC:976(H)×494(V)	720P	PAL:976(H)×582(V), NTSC:976(H)×494(V)	PAL:976(H)×582(V), NTSC:976(H)×494(V)
Horizontal Resolution	600TVL	600TVL	700TVL	800TVL	1000TVL	700TVL	700TVL
Minimum illuminator	Color Model:0.003(0.6)lux(Sens-up OFF),B/W Model:0.0001(0.1)lux(Sens-up OFF)					0.01LUX/F1.2	0.01LUX/F1.2
S/N(Y Signal)	>58dB					>65dB(AGC OFF)	
AES	1/50-1/60,000sec(PAL),1/60-1/60,000sec(NTSC)						
WDR	—	—	—	—	—	D-WDR	D-WDR
DNR	—	—	—	—	—	2D-DNR	2D-DNR
OSD	—	—	—	—	—	OSD	OSD
White Balance	ATW/AWC/Manual/Outdoor(1,800°K~10,500°K)Indoor(4,500°K~8,500°K)						
AGC	AUTO					Auto/Manual/Off	
BLC	ON					ON/OFF	
Gamma Adjusting	0.45						
synchronization System	Internal Synchronization						
Video Output	1.0Vp-p,75Ω						
Voltage	DC12V (9V ~ 15V)						
Operating Enviroment	-20°C~60°C / 10% ~ 95%RH						

● PRODUCT PICTURE

M TEAM



● FACTORY & OFFICE

M TEAM



● EXHIBITIONS

