

## ● FEATURES

- 1) outdoor IP66, mini 4.2" speed dome camera, Pan continuously 360° rotate, tilt 90°, rotation with auto-flip, Horizontal Speed  $\square 0.1^{\circ} \square 300^{\circ}/s \square$ , Vertical Speed  $\square 0.1^{\circ} \square 180^{\circ}/s \square$
- 2) Built-in 10X automatic integrated moduel, more convenient and flexible operation
- 3) 128 presets, 4 tour, 4 scan, 4 patterns, clock function 8 programmable zones with editable title, preset precision degree  $0.01^{\circ}$
- 4) Real time, temperature display , Low temperature protected function
- 5) Support privacy masking zone , 3D-NR
- 6) Lightningproof design, provide subtle Lightning Protection Indoor, IR range  $\square 35$  to 40 m, constant current control, synchronous switch

## ● SPECS

Model No.	All-in-one Camera	Specification
MVT-MO502	1/3 inch, Sony Effio-E CCD 10x 700TVL, No ICR	<ul style="list-style-type: none"> <li>• Indoor, IR range <math>\square 35</math> to 40 m, constant current control, synchronous switch</li> <li>• indoor mini 4.2" speed dome camera, Pan continuously 360° rotate, tilt 90°, rotation with auto-flip, Horizontal Speed <math>\square 0.1^{\circ} \square 300^{\circ}/s \square</math>, Vertical Speed <math>\square 0.1^{\circ} \square 180^{\circ}/s \square</math></li> </ul>
MVT-MO503	1/3 inch, CMOS 10x 600TVL, with ICR	<ul style="list-style-type: none"> <li>• Built-in 10X automatic integrated moduel, more convenient and flexible operation</li> <li>• 128 presets, 4 tour, 4 scan, 4 patterns, clock function 8 programmable zones with editable title, preset precision degree <math>0.01^{\circ}</math></li> <li>• Real time, temperature display , Low temperature protected function</li> </ul>
MVT-MO504	1/3", COMS 1099, 700TVL, 6MM lens	<ul style="list-style-type: none"> <li>• Support privacy masking zone , 3D-NR</li> <li>• Lightningproof design, provide subtle Lightning Protection</li> </ul>



● EXHIBITIONS

