

● FEATURES

- 1) Indoor,IR range 35 to 40 m, constant current control,synchronous switch
- 2) indoor mini 4" speed doom camera,Pan continuously 360° rotate, tilt 90°, rotation with auto-flip, Horizontal Speed 0.1° 300°/s, Vertical Speed 0.1° 180°/s
- 3) Built-in 10X automatic integrated moduel, more convenient and flexible operation
- 4) 128 presets, 4 tour, 4 scan, 4 patterns, clock function 8 programmable zones with editable title, preset precision degree 0.01°
- 5) Real time, temperature display , Low temperature protected function
- 6) Support privacy masking zone ,3D-NR
- 7) Lightningproof design,provide subtle Lightning Protection
- 8)1/3 inch,sony 238 CMOS 1MP/720P 10x Optical Zoom ICR

● SPECS

PTZ Specs	
Manual speed	Pan 0.2° 300°/s
	Tilt 0.2° 180°/s
Power supply	DC 12V
Rotation	Pan continuously 360°, tilt 0° 90° with auto-flip
Speed Proportion	As the length of focus, to auto-adjust the speed
Preset	128 preset, title can be edited
Auto-flip	Tilt down 90°, with auto-flip 180°
Scan	355°programmable, 4 scan
Pattern	4 patterns, and each record time is not less than 180s
Tour	4 tour, and speed & park time of presets can be set.
Remote controlling	RS485
Baud rate (RS485)	2400 4800 9600/19200 bps

ID range	1-254
Power consumption	6W
Temperature	-10°C□+50°C/ -40°C□+60°C via heater & Fans (Optional)
Installation	Wall installation, ceiling installation
Net weight	1.8Kg
CAM SPEC	
Sensor	1/3" Sony 238 CMOS Sensor+NVP2431H
	1280×720
OPTICS	Optical x10,Zoom f = 5.1mm ~ 51mm
Angle	Appr. 55.2°(Wide) to 3.2°(Tele)
Min. Illumination	Color : 0.5 lux , BW : 0.1lux
S/N (Y signal)	52dB
White Balance	Auto
ICR	Manual/Auto
DNR	Auto / Off / Low / Middle / High
HLC	Off / On
Defog	Off / On
Max Gain	Auto
IRIS	Auto
FLIP	Vertical , Horizontal ,Vertical-Horizontal,OFF Selectable

● PRODUCT PICTURE

M' TEAM



● FACTORY & OFFICE

M' TEAM



● EXHIBITIONS

M' TEAM

