

Main Features:

- 1.0M/1.3M/2.0M pixel full real time optional,Highest resolution 1080P
- follow HD and CVBS video standard
- 6mm(M12) fixed Lens
- Water Resistant Rate:IP66
- support transmission distance above 500M under general 75- 3 coaxial cable without loss
- High-speed, long-distance, real-time transmission
- support OSD menu
- with ICR switching , to achieve Day and Night monitoring
- Used genuinely imported 3rd generation IR LEDs and megapixel high definition lens, these cameras have been featured as great performance in color restoration,image definition and night viewing.

Application Places:

Apply to the financial, supermarket, telecommunications, government, schools, airports, factories, hotels, museums and other places of requirement of high-definition.

Model	MVT-AH20E	MVT-AH20T	MVT-AH20B
Sensor	1/3" CMOS pixelplus 1.3M/ 1024P AR0131	1/3" CMOS pixelplus 1.3M/ 1024P AR0130	1/3" CMOS pixelplus 1.3M/ 1024P SONY225
SIGNAL	PAL / NTCS		
Video Output	HD-AHD/CVBS		
Effective Pixels	1280(H)*1024(V)	1280(H)*1024(V)	1280(H)*1024(V)
Min. Illumination	0.01Lux F1.2		
Shutter	4/25s~1/45,000s		
Synchronization	Internal		
Video Output	1-channel BNC HDAHD/CVBS high definition video output		
BLC	optional		
OSD	optional		
AWB	Automatic / manual / day / night		
Day/Night	Auto(ICR) / Color / B/W		
Transmission Distance	Over 500m via 75-3 coaxial cable		
Power Supply	DC 12V±10%		
Working Environment	30°C~+60°C/Less than 95%RH(no condensation)		
Power Consumption	4W MAX		



Blue color



White color



* Mini Style

- * Lens 3.6mm&6.0mm optional
- * IR LED 24pcs, IR 20m

firm bracket, angle adjustable

M TEAM

● FACTORY & OFFICE

M' TEAM



● EXHIBITIONS

M' TEAM

