

Outdoor 6mm Lens POE IP Camera Low Light CCTV Security Camera MVT-M1780S

Starlight IP Camera

Super Low-Light Effect (Under 0.001Lux)



STARLIGHT MOTION 1080P HD P2P POE

No light B/W Mode Low light Color Mode Daytime Clear Color Mode

FEATURES



- *Adopts Hisilicon DSP Hi3516CV300 plus Sony CMOS IMX291, resolution upto 1080P/2MP
- *Super good performance in low light environment, low illumination under 0.001Lux
- *Compression format
- *3MP 6mm lens(M12), 30m IR distance

Starlight IP camera VS Common Camera in low light environment.



If you want to view the real image quality of starlight ip camera, please check below video record.

Warmly notice: please do setup the player image quality to 1080p when watch the video.

MVTEAM Starlight IP Camera Clear Color Image at Dayti...



2017-12-13 11:09



-IPC

MVTEAM Starlight IP Camera Video Record(No Light)



2017-12-13 00:13



-IPC

▼ Pictures

M'TEAM



▼ 3-Axis Bracket

M'TEAM



▼ Size

M'TEAM



| | |
|-----------------------------|---|
| Model | MVT-M1780S |
| Sensor type | 1/2.8" SONY CMOS IMX291(Low illumination) |
| DSP | Hi3516CV300 |
| Compression format | H.264/JPEG/AVI/MJPEG |
| Resolution | 1080P 1920*1080 |
| Shutter speed | 1/50(1/60) ~ 1/100,000 s |
| Video compression | 32Kbps~16Mbps |
| Lens | Megapixel HD 6mm Lens |
| Lens Interface type | (M12) |
| Day and night switch system | IR-CUT |
| Audio Compression | ADPCM |
| WDR | Support DWDR |
| Minimum illumination | 0.001Lux |
| Image setting | Saturation,brightness,contrast ratio can be adjusted by CMS and IE browser |
| Intelligent alarm | Motion detecting, video loss,network cable disconnection, and IP address conflict |
| Memory Function | Network storage |
| Network Protocol | P2P,RTP,RTSP,TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP |
| General function | Flash-prevention, double stream, heartbeat, password protection |
| Communication interface | 1ch RJ45,10M/100M ethernet ports adaptively |
| LED | 42pcs IR leds |
| IR distance | 35m |
| ONVIF | Support ONVIF 2.4 |
| Power | DC 12V/1A Power adaptor or make POE on extension Video Cable |
| Operating Temperature | -10°C~50°C |

▼ Packages

Brand Camera Package



Neutral Camera Package



Brand DVR Package



Package: MVTEAM Brand Box Or Netural Box Or Specified by customer.



Shipping: Based on the your demands to choose the best shipping way.

Contact us:

If you have any question, welcome to **Contact us**.

Your close attention to our company is highly appreciated.

Welcome to visit our official website www.mvteamcctv.com to view video demos,download product catalog and read CCTV technical articles