

FEATURES



1. Economical Security camera
2. Good image quality and cheap price
3. Widely compatible, able to match AHD DVR and All Standalone DVR
4. Easy to operate, Plug and Play
5. Advanced CMS software supporting 3G remote view

SPECS



Model	MVT-R7341O	MVT-R7341F	MVT-R7341Z	MVT-R7341E	MVT-R7341A	MVT-R7351E	MVT-R7351F
Image Sensor	1/4" Color CMOS	1/3" Color CMOS	1/3" Color CMOS	1/4" Color CMOS	1/3" Color CMOS	1/3 sony CCD	1/3 sony CCD
TV System	PAL/NTSC						
Image Resolution	PAL:752(H)×582(V), NTSC:768(H)×494(V)	PAL:752(H)×582(V), NTSC:768(H)×494(V)	PAL:976(H)×582(V), NTSC:976(H)×494(V)	PAL:976(H)×582(V), NTSC:976(H)×494(V)	720P	PAL:976(H)×582(V), NTSC:976(H)×494(V)	PAL:976(H)×582(V), NTSC:976(H)×494(V)
Horizontal Resolution	600TVL	600TVL	700TVL	800TVL	1000TVL	700TVL	700TVL
Minimum illuminator	Color Model:0.003(0.6)lux(Sens-up OFF),B/W Model:0.0001(0.1)lux(Sens-up OFF)					0.01LUX/F1.2	0.01LUX/F1.2
S/N(Y Signal)	>58dB					>65dB(AGC OFF)	
AES	1/50-1/60,000sec(PAL),1/60-1/60,000sec(NTSC)						
WDR	—	—	—	—	—	D-WDR	D-WDR
DNR	—	—	—	—	—	2D-DNR	2D-DNR
OSD	—	—	—	—	—	OSD	OSD
White Balance	ATW/AWC/Manual/Outdoor(1,800°K~10,500°K)Indoor(4,500°K~8,500°K)						
AGC	AUTO					Auto/Manual/Off	
BLC	ON					ON/OFF	
Gamma Adjusting	0.45						
synchronization System	Internal Synchronization						
Video Output	1.0Vp-p,75Ω						
Voltage	DC12V (9V ~ 15V)						
Operating Environment	-20°C~60°C / 10% ~ 95%RH						



New Appearance CCTV Cameras



MVT-R46
8mm(CS) Lens,
42 pcs IR leds



MVT-R30
8mm Lens,
42pcs×Φ5 IR leds



MVT-R21
2.8-12mm
vari-focal Lens,
42pcs×Φ5 IR leds



MVT-R62
2.8-12mm
vari-focal Lens,
42pcs×Φ5 IR leds



MVT-R58
9-22mm
vari-focal Lens,
72pcs×Φ5 IR leds



MVT-D30
6mm lens,
24pcs×Φ5 IR leds



MVT-D22
6mm lens,
36pcs×Φ5 IR leds



MVT-D28
6mm lens,
36pcs×Φ5 IR leds



MVT-D29
2.8-12mm
vari-focal Lens,
36pcs×Φ5 IR leds



MVT-D26
2.8-12mm(M12)
vari-focal Lens

● FACTORY & OFFICE

M TEAM



● EXHIBITIONS

M TEAM



For more about Analog Products welcome to Visit [FAQ](#)