

**Main Features:**

- 1.0M/1.3M/2.0M pixel full real time optional, Highest resolution 1080P
- follow HD and CVBS video standard
- 6mm(M12) fixed Lens
- Water Resistant Rate: IP66
  
- support transmission distance above 500M under general 75- 3 coaxial cable without loss
  
- High-speed, long-distance, real-time transmission
- support OSD menu
- with ICR switching , to achieve Day and Night monitoring
  
- Used genuinely imported 3rd generation IR LEDs and megapixel high definition lens, these cameras have been featured as great performance in color restoration, image definition and night viewing.

**Application Places:**

Apply to the financial, supermarket, telecommunications, government, schools, airports, factories, hotels, museums and other places of requirement of high-definition.

Model	MVT-AH20A	MVT-AH20N
Sensor	1/4" CMOS pixelplus 1.0M/ 720P OV9712	1/4" CMOS pixelplus 1.0M/ 720P AR0141
SIGNAL	PAL / NTCS	
Video Output	HD-AHD/CVBS	
Effective Pixels	1280(H)*720(V)	1280(H)*720(V)
Min. Illumination	0.01Lux F1.2	
Shutter	4/25s~1/45,000s	
Synchronization	Internal	
Video Output	1-channel BNC HDAHD/CVBS high definition video output	
BLC	optional	
OSD	optional	
AWB	Automatic / manual / day / night	
Day/Night	Auto(ICR) / Color / B/W	
Transmission Distance	Over 500m via 75-3 coaxial cable	
Power Supply	DC 12V±10%	
Working Environment	30°C~+60°C/Less than 95%RH(no condensation)	

Power Consumption	4W MAX
-------------------	--------

● PRODUCT PICTURE



Blue color



White color



\* Mini Style

\* Lens 3.6mm&6.0mm optional  
\* IR LED 24pcs,IR 20m



firm bracket, angle adjustable

M TEAM

## ● FACTORY & OFFICE

M'TEAM



## ● EXHIBITIONS

M'TEAM

