FEATURES

- Adotta 4.0Megapixel Progressive Scan sensore CMOS con illuminazione bassa.
- Supporta rete di video H.264 HP H.265 4MP @15fps 3MP @25Risoluzione fps.
- VandalDome Proof (scatola di metallo)
- Built-in: 3.6mm o 6 millimetri megapixel, POE e DC12V, audio in / out, Night Vision 20 metri.
- RTSP standard e Flash Video supportati, supporto Internet Explorer, Firefox, Safari, Chrome, Opera, ecc
- Supporto bidirezionale Parlando tra fotocamera con il PC remoto o telefono cellulare attraverso Internet.
- Android e IOS P2P App gratuita, gratuito CMS.
- In primo piano su misura completa ONVIF Versione con buona Competibility con flusso principale terzo CMS e NVR

SPECS

Full HD, rete

- Alta DSP prestazioni usando H.265 Video Codice compressione.
- Ottimizzato intelligente algoritmo di codifica per di più Clear Video con larghezza di banda inferiore.

Qualità Trusted

- Full Metal Shell, Precisione Design, antivandalismo Housing design.
- Illuminazione Prottech con 6 kV, elettrostatica di 8KV con protezione Potenza assorbita.

Funzionalità completa

- Brevettato Housing Design, bene tenere Consisitent e facile per il soffitto fai da te e l'installazione a parete.
- Audio e video sorveglianza Misto Reggere.
- Bilit-in IEEE802.3af POE.

Features		POE, Audio In/Out Cable, Powerful IR, DC12V, ONVIF 2.4, Free CMS, P2P Mobile and PC Remote Access
Cameras	Solution	Hi3516D+OV4689
	Sensor	1/3" CMOS
	Min. Illumination (Color)	0.01Lux/F1.2
	Shutter	1/5s-1/50,000s
	Day&Night	IR-CUT Auto, Black, Color
	Images Settings	Images, D&N Mode, Automatic Iris, Metering, White Balance, Exposure, Shutter, Mirror, Noise
Codec	Video Resolution	4.0M(2592*1520)@15FPS, 3M@25FPS
	Codec	H..265
	Video Frames	Real Time, Max. 25fps
	Codec Mode	VBR/CBR
	Data Rate	Three Streams, Main: 1500kbps-8Mbps Sub: 50-1000kbps
	Frames	1-30 frame adjustable
	Record	Video and Audio Recording and Playback, MP4 Format
Network	Internet	QR Scan for Remote Surveillance, Free P2P, No Port Forwarding Needed. Free DDNS
	Network Video	Standard RTSP, FLASH
	Remote Access	QR Scan Free APP (iphone/Andriod Smartphone), WEB (IE/Safari/Chrome/Firefox/Opera), NVR, CMS
	Compatibility	Onvif 2.4 and latest version, Customized compatibility with main stream CMS and NVRs
	WIFI	NO
	POE	Inside, IEEE802.3af
	Network Protocol	P2P,RTP,RTSP,TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP
Advanced	System	Time Sync. (Auto/Mannual//NTP/PC/NVR/RTC) Online upgrade /Alarm /System Status Reports
	Audio&Video	Audio (G.711A/U) / Video (Three Streams) / Video Mask / Motion Detection
	Storage	NVR, Cloud
	Events/Security/Log	Events (Events Setting/Schedule Recording/Schedule FTP and Snapshot), Security (Filter of User and IP Address), Log (System/Alarm/Acceess etc.)
Hardware	Network Interfaces	RJ-45, 10/100Base-T
	Microphone	NO
	Audio via Cable	Audio In/Out, Talkback (G.711A, G.711U)
	Local Storage	NO
	Others	NO
	Application	Indoor and Outdoor
	Installation	Wall-mounting, Ceiling-mounting
	Accessories	CD: 01.User Manual ; 02.CMS and User Manual; 03.IPCManager Tool and User Manual.
		Others: Printed Quick-Start, Installation Location Lable, Installation Kits.
	Power Supply	DC12V & POE
	Work Temperature	-10℃-50℃
	Work Humidity	10%-90%
	Power Consumption	2 Watt

PRODUCT PICTURE

FACTORY & OFFICE

EXHIBITIONS