

**1080P@1 / 2.8 "SONY 2M CMOS 20 4.7 94.0 DWDR**

1 IR 7.0 120  
Max.25 / 1080 @ 30fps

2 368 IT 264&038; MJPEG

3 DWDR/ICR DNR 2D&038; 3D AWB AGC BLC

4 Web CMS

5 300° / 0° 360° 0° 90°

6 128; 4

7 &038;;

8 -10°C 50°C

9

[PTZ IP](#)

360° 90°	
----------	--

0.1° 50° / 0.1° 50°

IR 100

128;

&038;;

4

; PTZ

TVS

SPEC

LINUX RTOS 32 DSP TI DM368

32M 128M DDR2

264 0,1-6Mbps

2.0 @ 25fps 1-25 FPS

Resolution: 1920x720x1080, 1280x720, 640x360x480x270, 352x288, 320x240, 352x192, 320x192, 288x192, 256x192;  
I/O: RTSP / FTP / PPPoE / DHCP / DDNS / NTP / UPnP / WEB / OSD

SPEC

1/3" CMOS, 1920x1080, 58.16°-2.9°, 4.7mm, 94, 20, 0.02LUX, IRCF, DSP-8, UP/DOWN

10BASE-T / 100BASE-TX RJ45, 1920 \* 1080, 25/30 FPS, H.264 / MJPEG, ONVIF 2.4, TCP / IP, HTTP, DHCP, PPPoE, UDP, RTP / RTCP, DNS, DDNS, UPnP, SMTP, 0.2°/50°, 200°/S, 360°, 90°, 128, 90°, 180°, 355°, 4, PTZ, Motif, OSD, -20°C~60°C, 0~95%, IP66, AC24V / 3A 40W, IR, 6.5



## ● EXHIBITIONS

