

33X 2MP PTZ IP MVT-NO704

FEATURES



1080P 1/3" Panasonic CMOS 30fps 4.7 mm 155.0 mm WDR P2P

1 5.5" IR 120m
25 / 30fps @ 1080p

2 TI 368 H.264 & MJPEG

3 DWDR Day / Night ICR DNR 2D & 3D AWB AGC BLC

4 Web CMS

5 300° / s 0° 360° 0° 90°

6 128; 4

7

8 -10°C + 50°C

9

[IP PTZ](#)

SPECS



360° 90°	
0.1° 220° / s 0.1° 180° / s	
IR 100m	
128;	
4	
PTZ	
TVS	
SPEC	
OS	LINUX RTOS 32 DSP TI Davinci DM368
RAM	32M 128M DDR2

編碼格式	H.264
編碼率	0.1M-6Mbps
幀率	2.0@ 25fps 1-25 fps
分辨率	1920×1080 1280×720; 640×360,480×270,352×288,320×240,352×192,320×192,288×192,256×192;
接口	IO IP
協議	RTSP / FTP / PPPOE / DHCP / DDNS / NTP / UPnP
功能	WEB OSD
平台	UC2 VM6000 SDK
鏡頭	1 / 2.8 " CMOS 34222
分辨率	1920×1080
視角	58.16°-2.9°
尺寸	4.7 mm 155mm
像素	33
照度	0.02LUX
功能	WDR
IRcf	Auto * / Manu
距離	1.0m 0.01m
功能	DSP-8
IRcf	Auto * / Manu R / B UP DOWN
功能	Auto * / Manu
接口	10Base-T / 100Base-TX RJ45
分辨率	1920 * 1080p
幀率	25/30 fps
編碼	H.264 / MJPEG
協議	Onvif 2.4 Ver
協議	TCP / IP.HTTP.DHCP.PPPoE.UDP.RTP / RTCP.DNS.DDNS .UPnP.SMTP
視角	0.2° 200° / s 0.2° 100° / s
速度	200° / S
旋轉	360°; 0° 90°
功能	
分辨率	128
視角	180° 90°
速度	355° 4
速度	4
功能	PTZ
功能	
功能	
OSD	
功能	
溫度	-20°C + 60°C
速度	0 95

防护等级	IP66
功率	AC24V / 40W
重量	6.5kg

● PRODUCT PICTURE



● FACTORY & OFFICE





www.mvteamcct.com