

## ● FEATURES

- 1) OSD
- 2) Speed(0.1°~220°/s) Speed(0.1°~180°/s)
- 3) 100 m
- 4)
- 5) 128 ( ) & ( )
- 6) 360 ° 90 ° : 0.4 ° 320 °/s
- 7) 8 4 180 s
- 8) 4
- 9)
- 10) Humanize
- 11)
- 12) OSD
- 13)
- 14) (Rs485)
- 15) PELCO-D PELCO-P
- 16) IP66
- 17) TVS4000V

## ● SPECS

PTZ	
Speed	0.1 °~220 °/s
Speed	0.1 °~180 °/s
Zoom	220 °/s
Range	360 ° 90 °
Resolution	128
Zoom	90 ° 180 °
Zoom	355 ° 4
Zoom	8
Zoom	
Zoom	BNC AHD
Zoom	RS485
Zoom (RS485)	2400~4800~9600/19200 bps
ID	1~254
Temp	-10°C~+60°C
Humidity	0~95%
Protection	IP66
Power	DC 12 V/5 A
Power	50 W

°C	-10°C~+60°C
kg	6.9 kg
Spec(20X,1.3MP)	
CMOS	1/3" CMOS 1305(H) × 1049(V) 1.37 M
	φ x18 f = 4.7 mm ~ 84.6.0 mm
	55.2°(Wide) 3.2°(Tele)
	: 0.5 , BW : 0.1
S/N (Y)	52dB
ICR	
DNR	/ / / /
	/
	/
	, ,

● PRODUCT PICTURE



## ● FACTORY & OFFICE

M' TEAM



## ● EXHIBITIONS

M' TEAM

