

FEATURES

M'TEAM

360° 90° 0.2° 300°/s
 LED 40
 128
 & 038
 4
 OSD
 RS485
 PELCO-D PELCO-P
 TVS DC12V IP66

SPECS

M'TEAM

PTZ	
Horizontal Pan	0.2° 300°/s
	0.2° 180°/s
Power	DC 12V
Angle	360° 0° 90°
Zoom	4
Resolution	128
Field of View	90° 180°
Temperature	355° 4
Storage	4 180S
Protocol	4 & 038
Remote	RS485
RS485	2400/4800/19200 9600 BPS
ID	1-254
Power	6W
Temp	-10°C 50°C / -40°C 60°C & 038
Resolution	1.8
CAM	

感測器	1/3 " 322 CMOS 感測器+ SONY4191 ISP
	* 1080 1920
鏡頭	10mm X10mm F = 5.1mm 51mm
視角	APPR 55.2° 3.2°
最低照度	0.5 lux BW 0.1lux
S / N 比率	52dB
紅外線	紅外線
ICR	紅外線/紅外線
DNR	紅外線 / 紅外線 / 紅外線 / 紅外線
HLC	紅外線 / 紅外線
紅外線	紅外線
紅外線	紅外線
FLIP	紅外線 OFF 紅外線

● PRODUCT PICTURE

M TEAM



● FACTORY & OFFICE

M TEAM



● EXHIBITIONS

M TEAM



██████████ AHD ████████████████████ ██████████